

屋内照明器具特性	
品番 (品名)	XAS7310N
光源	LED5000_70_1020 ×1 1020.0 lm
管理番号	K0171001 (1) DY 1
BZ分類	BZ4/1.1/BZ3/3.5/BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		4 1 % 5 9 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 2	3 5	3 0	5 0	4 0	3 4	2 9	4 4	3 6	3 0	2 7	3 8	3 2	2 7	2 4	2 0
			0 . 6 3	0 . 8	6 2	5 2	4 5	4 0	5 9	4 9	4 3	3 8	5 1	4 4	3 9	3 5	4 5	3 9	3 5	3 2	2 6
			0 . 5 6	1 . 0	6 9	5 9	5 2	4 7	6 4	5 6	5 0	4 5	5 7	5 0	4 5	4 1	4 9	4 4	4 1	3 8	3 1
				1 . 2 5	7 4	6 6	5 9	5 4	7 0	6 2	5 7	5 2	6 1	5 5	5 1	4 7	5 3	4 9	4 6	4 3	3 5
下方投影面積		cm ²	1 . 5	7 8	7 0	6 4	6 0	7 3	6 7	6 1	5 7	6 4	5 9	5 5	5 2	5 6	5 2	4 9	4 7	3 8	
等価発光面積		cm ²	2 . 0	8 3	7 7	7 2	6 7	7 8	7 3	6 8	6 4	6 9	6 4	6 1	5 8	6 0	5 7	5 4	5 2	4 2	
取付 高さ	器具間隔最大限		2 . 5	8 6	8 1	7 6	7 2	8 1	7 6	7 2	6 9	7 1	6 8	6 5	6 2	6 2	6 0	5 7	5 5	4 5	
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 4	8 0	7 6	8 3	7 9	7 5	7 2	7 3	7 0	6 7	6 5	6 4	6 2	6 0	5 8	4 7	
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	9 1	8 7	8 4	8 1	8 6	8 3	8 0	7 7	7 6	7 3	7 1	6 9	6 6	6 4	6 3	6 1	5 0	
			5 . 0	9 3	9 0	8 7	8 4	8 7	8 5	8 2	8 0	7 7	7 5	7 3	7 2	6 7	6 6	6 5	6 3	5 1	
			7 . 0	9 5	9 2	9 0	8 8	8 9	8 7	8 5	8 4	7 9	7 7	7 6	7 5	6 9	6 8	6 7	6 6	5 3	
			1 0 . 0	9 6	9 4	9 3	9 1	9 1	8 9	8 8	8 7	8 0	7 9	7 8	7 7	7 0	6 9	6 9	6 8	5 5	

