

屋内照明器具特性	
品番 (品名)	L S L G 9 0 6
光源	LLD2000LSCE1 ×1 531.0 lm
管理番号	K0175300 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		41 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		20 % 21 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.63	0.6	21	16	13	11	19	15	12	10	16	13	11	9	13	11	9	8	6
			0.6	0.8	24	20	17	15	23	19	16	14	19	16	14	13	16	14	12	11	8
			1.0	27	23	20	18	25	22	19	17	21	19	17	15	18	16	14	13	10	
			0.56	1.25	29	26	23	21	27	24	22	20	23	21	19	17	19	18	16	15	12
下方投影面積 等価発光面積		cm ² cm ²	1.5	31	28	25	23	29	26	24	22	25	22	21	19	21	19	18	17	13	
			2.0	33	30	28	26	31	28	26	25	26	25	23	22	22	21	20	19	14	
取付 高さ	器具間隔最大限		2.5	34	32	30	29	32	30	28	27	27	26	25	23	23	22	21	20	15	
	横方向 (A) 縦方向 (B)		3.0	35	33	32	30	33	31	30	28	28	27	26	25	24	23	22	21	16	
H _m	0.00 H _m	1.67 H _m	4.0	37	35	34	32	34	33	31	30	29	28	27	26	25	24	23	23	17	
			5.0	37	36	35	34	35	34	33	32	30	29	28	27	25	25	24	24	18	
			7.0	38	37	36	35	36	35	34	33	31	30	29	29	26	25	25	25	18	
			10.0	39	38	37	37	36	35	35	34	31	31	30	30	26	26	26	25	19	

