

屋内照明器具特性	
品番 (品名)	L S L G 9 0 7
光源	L L D 4 0 0 0 L S C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 4 1 5 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4

器具効率		4 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		2 2 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		2 1 %																					
保守率		良 中 否	0 . 6 3	0 . 6	2 1	1 7	1 4	1 1	2 0	1 6	1 3	1 1	1 7	1 3	1 1	1 0	1 4	1 1	1 0	8	6		
			0 . 6	0 . 8	2 5	2 1	1 8	1 6	2 4	2 0	1 7	1 5	2 0	1 7	1 5	1 3	1 7	1 4	1 3	1 1	9		
			0 . 5 6	1 . 0	2 8	2 4	2 1	1 9	2 6	2 2	2 0	1 8	2 2	1 9	1 7	1 6	1 9	1 6	1 5	1 4	1 0		
				1 . 2 5	3 1	2 7	2 4	2 2	2 8	2 5	2 3	2 1	2 4	2 2	2 0	1 8	2 0	1 8	1 7	1 6	1 2		
下方投影面積		c m ²	1 . 5	3 2	2 9	2 6	2 4	3 0	2 7	2 5	2 3	2 5	2 3	2 1	2 0	2 1	2 0	1 8	1 7	1 3			
等価発光面積			c m ²	2 . 0	3 5	3 2	2 9	2 7	3 2	3 0	2 8	2 6	2 7	2 5	2 4	2 3	2 3	2 2	2 1	2 0	1 5		
取付高さ	器具間隔最大限		2 . 5	3 6	3 4	3 1	3 0	3 3	3 1	2 9	2 8	2 8	2 7	2 6	2 4	2 4	2 3	2 2	2 1	1 6			
	横方向 (A)		縦方向 (B)	3 . 0	3 7	3 5	3 3	3 1	3 4	3 2	3 1	2 9	2 9	2 8	2 7	2 6	2 5	2 4	2 3	2 2	1 7		
H m	0 . 0 0 H m		1 . 6 7 H m	4 . 0	3 8	3 6	3 5	3 4	3 5	3 4	3 3	3 2	3 0	2 9	2 8	2 7	2 6	2 5	2 4	2 3	1 8		
				5 . 0	3 9	3 7	3 6	3 5	3 6	3 5	3 4	3 3	3 1	3 0	2 9	2 9	2 6	2 5	2 5	2 4	1 8		
				7 . 0	4 0	3 9	3 8	3 7	3 7	3 6	3 5	3 4	3 2	3 1	3 0	3 0	2 7	2 6	2 6	2 5	1 9		
				1 0 . 0	4 0	4 0	3 9	3 8	3 8	3 7	3 6	3 6	3 2	3 2	3 1	3 1	2 7	2 7	2 7	2 6	2 0		

