

屋内照明器具特性	
品番 (品名)	L S E B 3 2 3 9
光源	LED2700_70_337 x1 337.0 lm
管理番号	K0145063 (0) DB 1
B Z 分類	BZ3 / 0.9 / BZ4 / 1.8 / BZ5 / 8.5 / BZ6

器具効率		100 % 上方光束 25 % 下方光束 75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
					床	10 %				10 %				10 %				10 %				0 %	
						室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	60	50	44	39	58	49	42	38	53	46	40	37	49	43	38	35	32		
			0.63	0.8	67	57	50	46	64	55	49	44	59	52	46	42	54	48	44	40	36		
			0.56	1.0	72	62	56	51	69	60	54	49	63	56	51	47	58	52	48	44	39		
			0.56	1.25	76	68	61	56	73	65	59	54	67	60	55	51	61	56	52	48	43		
下方投影面積		cm ²	1.5	80	71	65	60	76	69	63	58	69	63	59	55	63	59	55	51	45			
等価発光面積			cm ²	2.0	84	77	71	66	81	74	69	64	73	68	64	60	67	63	59	56	49		
				2.5	87	81	75	71	83	78	73	69	76	71	68	64	69	66	62	60	52		
取付 高さ	器具間隔最大限		3.0	89	84	79	74	85	80	76	72	78	74	70	67	71	68	65	62	55			
	横方向 (A)			縦方向 (B)		4.0	92	87	83	80	88	84	80	77	81	77	74	71	74	71	68	66	58
H m	1.06 H m		1.07 H m		5.0		94	90	86	83	90	86	83	80	82	79	77	74	75	73	71	69	60
			7.0	96			93	90	87	92	89	87	84	84	82	80	78	77	75	74	72	63	
				10.0			98	95	93	91	94	92	90	88	86	84	83	81	79	78	76	75	66

