

屋内照明器具特性	
品番 (品名)	L S E W C 4 0 7 0
光源	LED2700_70_515 ×1 515.0 lm
管理番号	K0171392 (0) DB 1
B Z 分類	BZ9 / 0.9 / BZ8

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		4 9 %																					
保守率		良 中 否	0 . 6 3	0 . 6	4 5	3 2	2 4	1 9	4 1	2 9	2 2	1 7	3 3	2 4	1 9	1 4	2 6	2 0	1 5	1 1	6		
			0 . 6	0 . 8	5 3	4 1	3 2	2 6	4 8	3 7	3 0	2 4	4 0	3 1	2 5	2 0	3 2	2 5	2 0	1 7	1 0		
			0 . 5 6	1 . 0	5 9	4 7	3 9	3 2	5 4	4 3	3 6	3 0	4 4	3 6	3 0	2 5	3 5	2 9	2 4	2 1	1 3		
				1 . 2 5	6 4	5 4	4 5	3 9	5 9	4 9	4 2	3 6	4 8	4 1	3 5	3 0	3 9	3 3	2 9	2 5	1 6		
下方投影面積		c m ²		1 . 5	6 9	5 8	5 0	4 4	6 3	5 4	4 7	4 1	5 2	4 5	3 9	3 4	4 2	3 6	3 2	2 8	1 8		
等価発光面積			c m ²	2 . 0	7 4	6 5	5 8	5 2	6 8	6 0	5 4	4 8	5 6	5 0	4 5	4 1	4 6	4 1	3 7	3 4	2 2		
取付 高さ	器具間隔最大限			2 . 5	7 8	7 0	6 3	5 8	7 2	6 5	5 9	5 4	6 0	5 4	5 0	4 5	4 8	4 4	4 1	3 8	2 5		
	横方向 (A)		縦方向 (B)	3 . 0	8 0	7 3	6 7	6 2	7 4	6 8	6 2	5 8	6 2	5 7	5 3	4 9	5 1	4 7	4 4	4 1	2 7		
H m	1 . 6 2 H m	1 . 8 6 H m		4 . 0	8 4	7 8	7 3	6 8	7 7	7 2	6 8	6 4	6 5	6 1	5 7	5 4	5 3	5 0	4 8	4 5	3 1		
				5 . 0	8 6	8 1	7 7	7 3	8 0	7 5	7 1	6 8	6 7	6 4	6 0	5 8	5 5	5 3	5 0	4 8	3 3		
				7 . 0	8 9	8 5	8 1	7 8	8 2	7 9	7 6	7 3	7 0	6 7	6 4	6 2	5 8	5 6	5 4	5 2	3 6		
				1 0 . 0	9 1	8 8	8 5	8 3	8 4	8 2	7 9	7 7	7 2	7 0	6 8	6 6	6 0	5 8	5 7	5 5	3 9		

