

屋内照明器具特性	
品番 (品名)	L S E W C 4 0 7 3
光源	LED2700_70_175 ×1 175.0 l m
管理番号	K0171394 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		4 9 %																					
保守率		良 中 否	0 . 6 3	0 . 6	4 8	3 6	2 9	2 4	4 4	3 4	2 7	2 2	3 7	2 9	2 3	1 9	3 0	2 4	2 0	1 7	1 1		
			0 . 6	0 . 8	5 7	4 6	3 8	3 2	5 2	4 2	3 5	3 0	4 4	3 6	3 1	2 6	3 6	3 0	2 6	2 3	1 6		
				1 . 0	6 3	5 2	4 5	3 9	5 8	4 8	4 2	3 7	4 8	4 1	3 6	3 2	4 0	3 4	3 0	2 7	1 9		
			0 . 5 6	1 . 2 5	6 8	5 9	5 1	4 6	6 3	5 4	4 8	4 3	5 3	4 6	4 1	3 7	4 3	3 9	3 5	3 1	2 2		
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	7 2	6 3	5 6	5 1	6 7	5 9	5 3	4 8	5 6	5 0	4 5	4 1	4 6	4 2	3 8	3 5	2 5		
				2 . 0	7 8	7 0	6 4	5 9	7 2	6 5	6 0	5 5	6 0	5 5	5 1	4 7	5 0	4 6	4 3	4 0	2 9		
				2 . 5	8 1	7 4	6 9	6 4	7 5	6 9	6 4	6 0	6 3	5 9	5 5	5 2	5 2	4 9	4 6	4 4	3 1		
取付 高さ	器具間隔最大限			3 . 0	8 3	7 8	7 3	6 8	7 7	7 2	6 8	6 4	6 5	6 1	5 8	5 5	5 4	5 1	4 9	4 7	3 3		
	横方向 (A)	縦方向 (B)		4 . 0	8 7	8 2	7 8	7 4	8 0	7 6	7 2	6 9	6 8	6 5	6 2	6 0	5 7	5 4	5 2	5 0	3 6		
H m	1 . 3 7 H m	1 . 2 5 H m		5 . 0	8 8	8 5	8 1	7 8	8 2	7 9	7 5	7 3	7 0	6 7	6 5	6 2	5 8	5 6	5 4	5 3	3 8		
				7 . 0	9 1	8 8	8 5	8 2	8 4	8 2	7 9	7 7	7 2	7 0	6 8	6 6	6 0	5 8	5 7	5 6	4 0		
				1 0 . 0	9 3	9 0	8 8	8 6	8 6	8 4	8 2	8 0	7 3	7 2	7 1	6 9	6 1	6 0	5 9	5 8	4 2		

