

屋内照明器具特性	
品番 (品名)	X S L G 1 0 1 L S
光源	LED2700_70_200 ×1 200.0 lm
管理番号	K0169173 (1) DR 1
B Z 分類	B Z 4

器具効率		100 % 上方光束 30 % 下方光束 70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	55	44	37	32	52	42	36	31	47	39	33	29	42	36	31	28	24
			0.6	0.8	65	54	47	42	61	52	46	41	55	48	42	38	50	44	39	36	31
			0.56	1.0	71	61	55	49	67	59	53	48	61	54	49	45	55	49	45	42	37
				1.25	76	68	61	56	73	65	59	55	66	60	55	51	59	55	51	48	42
下方投影面積		cm ²		1.5	80	73	67	62	76	70	64	60	69	64	59	56	62	58	55	52	45
			等価発光面積		cm ²	2.0	85	79	74	69	81	76	71	67	74	69	65	62	67	63	60
取付	器具間隔最大限			2.5	89	83	78	75	84	80	75	72	77	73	70	67	69	66	64	62	53
高さ	横方向 (A)		縦方向 (B)	3.0	91	86	82	78	86	82	79	75	79	75	72	70	71	69	66	64	56
H m	1.15 H m	1.26 H m	4.0	93	90	86	83	89	86	83	80	81	78	76	74	73	71	70	68	59	
			5.0	95	92	89	87	91	88	86	83	83	80	79	77	75	73	72	70	61	
			7.0	97	95	93	91	93	91	89	87	84	83	81	80	77	75	74	73	63	
			10.0	98	97	95	94	94	93	91	90	86	85	84	83	78	77	76	75	65	

