

屋内照明器具特性	
品番 (品名)	X S L G 1 0 2 L S
光源	LED2700_70_145 ×1 145.0 l m
管理番号	K0169174 (0) DR 1
B Z 分類	BZ4 / 0.9 / BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	55	44	37	32	52	42	36	31	47	39	33	29	42	36	31	28	24
			0.6	0.8	65	54	47	42	61	52	46	41	55	48	43	39	50	44	39	36	31
			0.56	1.0	71	62	55	50	67	59	53	48	61	54	49	45	55	49	45	42	37
				1.25	77	68	62	57	73	65	59	55	66	60	55	51	59	55	51	48	41
下方投影面積 等価発光面積		cm ²		1.5	80	73	67	62	76	70	64	60	69	64	59	56	62	58	55	52	45
				2.0	85	79	74	70	81	76	71	67	74	69	65	62	66	63	60	58	50
				2.5	89	83	79	75	84	80	76	72	76	73	69	67	69	66	64	61	53
				3.0	91	86	82	79	86	82	79	76	78	75	72	70	71	68	66	64	55
H _m	1.15 H _m	1.25 H _m		4.0	93	90	86	84	89	86	83	80	81	78	76	74	73	71	69	68	58
				5.0	95	92	89	87	91	88	86	83	82	80	78	77	74	73	71	70	60
				7.0	97	95	93	91	92	91	89	87	84	83	81	80	76	75	74	73	63
				10.0	98	97	95	94	94	92	91	90	85	84	83	82	77	77	76	75	64

