

屋内照明器具特性	
品番 (品名)	X S L G 1 0 7 L S
光源	LED2700_70_215 ×1 215.0 l m
管理番号	K0169180 (1) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	50	39	32	27	46	36	30	25	39	32	26	23	33	27	23	20	15
			0.6	0.8	60	49	42	37	55	46	39	35	47	40	35	31	39	34	30	27	20
			0.56	1.0	66	56	49	44	61	52	46	42	52	45	41	37	43	39	35	32	24
				1.25	71	63	56	51	66	59	53	48	56	51	46	43	47	43	40	37	28
下方投影面積		cm ²		1.5	75	67	61	56	70	63	57	53	59	54	50	47	50	46	43	41	31
等価発光面積			cm ²	2.0	80	74	69	64	75	69	64	60	64	60	56	53	54	51	48	46	35
				2.5	84	78	73	69	78	73	69	65	66	63	60	57	56	53	51	49	37
取付	器具間隔最大限			2.5	84	78	73	69	78	73	69	65	66	63	60	57	56	53	51	49	37
高さ	横方向 (A)		縦方向 (B)	3.0	86	81	77	73	80	76	72	69	68	65	63	60	58	55	53	52	39
H m	0.00 H m		1.67 H m	4.0	89	85	81	78	83	79	76	74	71	68	66	64	60	58	56	55	41
				5.0	90	87	84	82	84	81	79	77	72	70	68	67	61	60	58	57	43
				7.0	92	90	88	86	86	84	82	80	74	72	71	70	62	61	60	59	44
				10.0	94	92	91	89	87	86	85	83	75	74	73	72	64	63	62	61	46

