

屋内照明器具特性	
品番 (品名)	X S L G 1 0 1 V S
光源	L E D 3 5 0 0 _ 7 0 _ 2 0 0 × 1 2 0 0 . 0 l m
管理番号	K 0 1 6 9 1 7 3 (1) D R 1
B Z 分類	B Z 4

器具効率		1 0 0 % 上方光束 3 0 % 下方光束 7 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
				室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	5 5	4 4	3 7	3 2	5 2	4 2	3 6	3 1	4 7	3 9	3 3	2 9	4 2	3 6	3 1	2 8	2 4
			0 . 6	0 . 8	7 1	6 1	5 5	4 9	6 7	5 9	5 3	4 8	6 1	5 4	4 9	4 5	5 5	4 9	4 5	4 2	3 7		
			0 . 5 6	1 . 2 5	7 6	6 8	6 1	5 6	7 3	6 5	5 9	5 5	6 6	6 0	5 5	5 1	5 9	5 5	5 1	4 8	4 2		
			1 . 5	8 0	7 3	6 7	6 2	7 6	7 0	6 4	6 0	6 9	6 4	5 9	5 6	6 2	5 8	5 5	5 2	4 5			
下方投影面積		c m ² 等価発光面積	2 . 0	8 5	7 9	7 4	6 9	8 1	7 6	7 1	6 7	7 4	6 9	6 5	6 2	6 7	6 3	6 0	5 8	5 0			
等価発光面積			2 . 5	8 9	8 3	7 8	7 5	8 4	8 0	7 5	7 2	7 7	7 3	7 0	6 7	6 9	6 6	6 4	6 2	5 3			
高さ			3 . 0	9 1	8 6	8 2	7 8	8 6	8 2	7 9	7 5	7 9	7 5	7 2	7 0	7 1	6 9	6 6	6 4	5 6			
H m			4 . 0	9 3	9 0	8 6	8 3	8 9	8 6	8 3	8 0	8 1	7 8	7 6	7 4	7 3	7 1	7 0	6 8	5 9			
			5 . 0	9 5	9 2	8 9	8 7	9 1	8 8	8 6	8 3	8 3	8 0	7 9	7 7	7 5	7 3	7 2	7 0	6 1			
			7 . 0	9 7	9 5	9 3	9 1	9 3	9 1	8 9	8 7	8 4	8 3	8 1	8 0	7 7	7 5	7 4	7 3	6 3			
			1 0 . 0	9 8	9 7	9 5	9 4	9 4	9 3	9 1	9 0	8 6	8 5	8 4	8 3	7 8	7 7	7 6	7 5	6 5			

