

屋内照明器具特性	
品番 (品名)	NNN7 4 5 0 0 K
光源	NNU240105KLE9 ×1 2050.0 l m
管理番号	K0190843 (1) DB 1
B Z 分類	B Z 2

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 79 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.77	0.6	54	46	41	38	53	46	41	38	51	45	41	38	50	44	40	38	36	
			0.72	0.8	61	54	50	46	60	54	49	46	58	53	49	46	57	52	49	46	45	
			0.68	1.0	66	60	55	52	65	59	55	52	63	58	55	52	61	57	54	51	50	
			1.25	70	64	60	57	69	64	60	57	67	63	59	57	65	62	59	56	55		
下方投影面積		cm ²	1.5	72	67	64	61	71	67	63	61	69	66	63	60	68	64	62	60	58		
等価発光面積			cm ²	2.0	75	72	69	66	74	71	68	66	73	70	67	65	71	68	66	64	63	
				2.5	77	74	72	69	76	74	71	69	75	72	70	68	73	71	69	67	66	
取付高さ	器具間隔最大限		3.0	79	76	74	72	78	75	73	71	76	74	72	70	74	72	71	69	68		
	横方向 (A) 縦方向 (B)			4.0	80	78	76	75	79	77	76	74	78	76	74	73	76	74	73	72	70	
H m	1.11 H m	1.11 H m	5.0	81	80	78	77	80	79	77	76	79	77	76	75	77	76	75	74	72		
			7.0	82	81	80	79	81	80	79	78	80	79	78	77	78	77	76	76	74		
			10.0	83	82	81	81	82	81	81	80	80	80	79	78	79	78	77	77	75		

