

屋内照明器具特性	
品番 (品名)	XAS7302V
光源	LED3500_70_1115 ×1 1115.0 lm
管理番号	K0171369 (0) D 1
BZ分類	BZ5/0.7/BZ4/2.3/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		4 4 % 5 6 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	5 2	4 0	3 3	2 8	4 8	3 8	3 2	2 7	4 2	3 4	2 8	2 4	3 6	2 9	2 5	2 2	1 7
			0 . 6 3	0 . 8	6 1	5 0	4 3	3 8	5 6	4 7	4 1	3 6	4 9	4 2	3 6	3 2	4 2	3 6	3 2	2 9	2 3
			1 . 0	6 7	5 7	5 0	4 4	6 2	5 4	4 7	4 2	5 4	4 7	4 2	3 8	4 6	4 1	3 7	3 4	2 7	
			0 . 5 6	1 . 2 5	7 2	6 3	5 6	5 1	6 7	5 9	5 3	4 9	5 8	5 2	4 8	4 4	5 0	4 5	4 2	3 9	3 1
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 6	6 8	6 1	5 6	7 1	6 4	5 8	5 3	6 1	5 6	5 1	4 8	5 3	4 9	4 5	4 2	3 3	
			2 . 0	8 1	7 4	6 8	6 4	7 6	7 0	6 5	6 0	6 6	6 1	5 7	5 4	5 6	5 3	5 0	4 7	3 7	
取付 高さ	器具間隔最大限		2 . 5	8 4	7 8	7 3	6 9	7 9	7 3	6 9	6 5	6 8	6 4	6 1	5 8	5 9	5 6	5 3	5 1	4 0	
	横方向 (A)	縦方向 (B)	3 . 0	8 6	8 1	7 7	7 3	8 1	7 6	7 2	6 9	7 0	6 7	6 4	6 1	6 0	5 8	5 6	5 3	4 2	
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	8 9	8 5	8 1	7 8	8 4	8 0	7 7	7 4	7 3	7 0	6 7	6 5	6 3	6 0	5 9	5 7	4 5	
			5 . 0	9 1	8 7	8 4	8 1	8 5	8 2	7 9	7 7	7 4	7 2	7 0	6 8	6 4	6 2	6 1	5 9	4 6	
			7 . 0	9 3	9 0	8 8	8 5	8 7	8 5	8 3	8 1	7 6	7 4	7 3	7 1	6 6	6 4	6 3	6 2	4 8	
			1 0 . 0	9 5	9 3	9 1	8 9	8 9	8 7	8 5	8 4	7 8	7 6	7 5	7 4	6 7	6 6	6 5	6 4	5 0	

