

屋内照明器具特性	
品番 (品名)	NY Y5 6 5 9 0
光源	LED9999_70_4300 ×1 4300.0 lm
管理番号	K0170521 (0) DB 1
BZ分類	BZ2 / 8.5 / BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	6 9	5 9	5 3	4 9	6 8	5 9	5 3	4 9	6 6	5 8	5 3	4 9	6 4	5 7	5 2	4 9	4 7	
			0 . 6 3	0 . 8	7 9	7 1	6 5	6 1	7 8	7 0	6 5	6 1	7 6	6 9	6 4	6 0	7 4	6 8	6 3	6 0	5 9	
			0 . 5 6	1 . 0	8 5	7 8	7 2	6 8	8 4	7 7	7 2	6 8	8 2	7 6	7 1	6 8	8 0	7 5	7 1	6 8	6 6	
				1 . 2 5	9 0	8 3	7 9	7 5	8 9	8 3	7 8	7 5	8 6	8 1	7 7	7 4	8 4	8 0	7 7	7 4	7 2	
下方投影面積		c m ²	1 . 5	9 3	8 7	8 3	7 9	9 2	8 6	8 2	7 9	8 9	8 5	8 1	7 8	8 7	8 4	8 0	7 8	7 6		
等価発光面積			c m ²	2 . 0	9 7	9 2	8 9	8 6	9 6	9 1	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 1	
取付高さ	器具間隔最大限		2 . 5	9 9	9 5	9 2	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 5		
	横方向 (A) 縦方向 (B)		3 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7		
H m	1 . 2 0 H m 1 . 2 0 H m		4 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 3	9 0		
			5 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 2		
			7 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 0	9 9	9 8	9 9	9 9	9 8	9 7	9 4		
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 9	9 6		

