

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 0 9
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176217 (0) DR 1
B Z 分類	B Z 5

器具効率		71 % 上方光束 3 % 下方光束 68 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	40	31	25	21	38	30	25	21	36	29	24	21	35	28	24	21	19				
			0.63	0.8	46	38	32	28	45	37	32	28	43	36	31	28	41	35	31	27	26				
			0.56	1.0	51	43	38	33	50	42	37	33	47	41	36	33	45	40	36	32	30				
			1.25	55	48	43	39	54	47	42	38	51	46	41	38	49	44	40	37	35					
下方投影面積		c m ²	1.5	58	52	47	43	57	51	46	42	54	49	45	42	52	47	44	41	39					
等価発光面積			c m ²	2.0	62	57	52	49	61	56	52	48	58	54	50	47	56	52	49	46	44				
取付高さ				器具間隔最大限		2.5	65	60	56	53	63	59	55	52	61	57	54	51	58	55	53	50	48		
横方向 (A)		縦方向 (B)		3.0	67	62	59	56	65	61	58	55	63	59	57	54	60	57	55	53	51				
H m	1.15 H m	1.15 H m	4.0	69	66	63	60	68	65	62	59	65	62	60	58	63	60	59	57	54					
			5.0	70	68	65	63	69	66	64	62	66	64	62	61	64	62	61	59	57					
			7.0	72	70	68	66	71	69	67	65	68	67	65	64	66	65	63	62	60					
			10.0	73	72	70	69	72	71	69	68	70	68	67	66	67	66	65	65	62					

