

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 7 9
光源	L L D 2 0 0 0 C U 1 × 1 5 6 6 . 0 l m
管理番号	K 0 1 7 9 0 3 7 (0) D R 1
B Z 分類	B Z 5

器具効率		9 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		4 % 9 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	5 2	4 0	3 3	2 7	5 1	4 0	3 2	2 7	4 8	3 8	3 2	2 7	4 5	3 7	3 1	2 7	2 4
			0 . 6 3	0 . 8	6 1	5 0	4 2	3 7	6 0	4 9	4 2	3 6	5 6	4 7	4 1	3 6	5 4	4 6	4 0	3 5	3 3
			1 . 0	6 8	5 7	4 9	4 3	6 6	5 6	4 9	4 3	6 2	5 4	4 7	4 2	5 9	5 2	4 6	4 2	3 9	
			0 . 5 6	1 . 2 5	7 3	6 3	5 6	5 0	7 1	6 2	5 5	5 0	6 8	6 0	5 4	4 9	6 4	5 8	5 2	4 8	4 5
下方投影面積		c m ²	1 . 5	7 7	6 8	6 1	5 6	7 5	6 7	6 0	5 5	7 1	6 4	5 9	5 4	6 8	6 2	5 7	5 3	5 0	
等価発光面積		c m ²	2 . 0	8 3	7 5	6 9	6 4	8 1	7 4	6 8	6 3	7 7	7 1	6 6	6 2	7 3	6 8	6 4	6 0	5 7	
取付 高さ	器具間隔最大限		2 . 5	8 6	7 9	7 4	6 9	8 4	7 8	7 3	6 8	8 0	7 5	7 1	6 7	7 7	7 2	6 9	6 5	6 2	
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 3	7 8	7 3	8 7	8 1	7 7	7 2	8 3	7 8	7 4	7 1	7 9	7 5	7 2	6 9	6 6	
H m	1 . 1 8 H m	1 . 1 8 H m	4 . 0	9 2	8 7	8 3	7 9	9 0	8 5	8 2	7 8	8 6	8 2	7 9	7 6	8 2	7 9	7 7	7 4	7 1	
			5 . 0	9 4	9 0	8 6	8 3	9 2	8 8	8 5	8 2	8 8	8 5	8 2	8 0	8 5	8 2	8 0	7 8	7 4	
			7 . 0	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 6	9 0	8 8	8 6	8 4	8 7	8 5	8 3	8 2	7 8	
			1 0 . 0	9 8	9 5	9 3	9 1	9 6	9 4	9 2	9 0	9 2	9 1	8 9	8 8	8 9	8 8	8 6	8 5	8 1	

