

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 7 9
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184424 (0) DR 1
B Z 分類	B Z 5

器具効率		69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		5 %	室指数	照明率 (X0.01)																	
下方光束		64 %		Z C M																	
保守率		良 中 否	0.67	0.6	38	29	24	20	37	29	24	20	34	28	23	20	33	27	22	19	18
			0.63	0.8	44	36	31	27	43	36	30	27	41	34	30	26	38	33	29	26	24
			0.56	1.0	49	41	36	32	47	40	35	32	45	39	34	31	42	37	33	30	28
				1.25	53	46	41	37	51	45	40	36	48	43	39	36	46	41	38	35	33
下方投影面積		c m ²		1.5	56	49	44	41	54	48	44	40	51	46	42	39	48	44	41	38	36
等価発光面積			c m ²	2.0	59	54	50	46	58	53	49	45	55	51	47	44	52	49	46	43	41
取付 高さ	器具間隔最大限		2.5	62	57	53	50	60	56	52	49	57	54	51	48	54	52	49	47	44	
	横方向 (A) 縦方向 (B)			3.0	63	59	56	53	62	58	55	52	59	56	53	51	56	54	51	49	46
H m	1.13 H m	1.13 H m	4.0	66	62	59	57	64	61	58	56	61	59	56	54	58	56	54	53	50	
			5.0	67	64	62	59	66	63	61	59	63	61	59	57	60	58	57	55	52	
			7.0	69	67	65	63	67	65	63	62	64	63	61	60	62	60	59	58	55	
			10.0	70	68	67	65	68	67	66	64	66	64	63	62	63	62	61	60	57	

