

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 1
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 6 4 8 4 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 2 . 3 / B Z 5

器具効率		4 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	2 7	2 2	1 8	1 6	2 7	2 1	1 8	1 5	2 5	2 1	1 8	1 5	2 4	2 0	1 7	1 5	1 4
			0 . 6 3	0 . 8	3 2	2 6	2 3	2 0	3 1	2 6	2 3	2 0	3 0	2 5	2 2	2 0	2 8	2 5	2 2	2 0	1 9
			0 . 5 6	1 . 0	3 5	3 0	2 6	2 4	3 4	2 9	2 6	2 4	3 2	2 8	2 6	2 3	3 1	2 8	2 5	2 3	2 2
				1 . 2 5	3 8	3 3	3 0	2 7	3 7	3 3	2 9	2 7	3 5	3 2	2 9	2 7	3 4	3 1	2 8	2 6	2 5
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	3 9	3 5	3 2	3 0	3 9	3 5	3 2	2 9	3 7	3 4	3 1	2 9	3 5	3 3	3 0	2 9	2 7
				2 . 0	4 2	3 9	3 6	3 4	4 1	3 8	3 5	3 3	3 9	3 7	3 5	3 3	3 8	3 6	3 4	3 2	3 1
				2 . 5	4 4	4 1	3 8	3 6	4 3	4 0	3 8	3 6	4 1	3 9	3 7	3 5	3 9	3 8	3 6	3 4	3 3
取付 高さ	器具間隔最大限			3 . 0	4 5	4 2	4 0	3 8	4 4	4 2	3 9	3 8	4 2	4 0	3 8	3 7	4 1	3 9	3 8	3 6	3 5
	横方向 (A)	縦方向 (B)		4 . 0	4 6	4 4	4 2	4 1	4 5	4 3	4 2	4 0	4 4	4 2	4 1	3 9	4 2	4 1	4 0	3 9	3 7
H m	0 . 8 5 H m	0 . 8 5 H m		5 . 0	4 7	4 5	4 4	4 2	4 6	4 5	4 3	4 2	4 5	4 3	4 2	4 1	4 3	4 2	4 1	4 0	3 8
				7 . 0	4 8	4 7	4 6	4 5	4 7	4 6	4 5	4 4	4 6	4 5	4 4	4 3	4 4	4 3	4 3	4 2	4 0
				1 0 . 0	4 9	4 8	4 7	4 6	4 8	4 7	4 6	4 6	4 6	4 6	4 5	4 4	4 5	4 4	4 4	4 3	4 2

