

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 1
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 5 0 7 (0) D R 1
B Z 分類	B Z 4 / 6 . 0 / B Z 5

器具効率		43 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	2 5	2 0	1 7	1 5	2 5	2 0	1 7	1 5	2 4	2 0	1 7	1 5	2 3	1 9	1 7	1 5	1 4				
			0 . 6 3	0 . 8	2 9	2 5	2 1	1 9	2 9	2 4	2 1	1 9	2 7	2 4	2 1	1 9	2 6	2 3	2 1	1 9	1 8				
			1 . 0	3 2	2 7	2 4	2 2	3 1	2 7	2 4	2 2	3 0	2 6	2 4	2 2	2 9	2 6	2 3	2 1	2 0					
			0 . 5 6	1 . 2 5	3 4	3 0	2 7	2 5	3 3	3 0	2 7	2 5	3 2	2 9	2 7	2 5	3 1	2 8	2 6	2 4	2 3				
下方投影面積		c m ²	1 . 5	3 6	3 2	2 9	2 7	3 5	3 2	2 9	2 7	3 4	3 1	2 9	2 7	3 2	3 0	2 8	2 6	2 5					
			2 . 0	3 8	3 5	3 3	3 1	3 7	3 5	3 2	3 0	3 6	3 4	3 2	3 0	3 5	3 3	3 1	2 9	2 8					
等価発光面積		c m ²	2 . 5	3 9	3 7	3 5	3 3	3 9	3 6	3 4	3 3	3 7	3 5	3 4	3 2	3 6	3 4	3 3	3 2	3 0					
			3 . 0	4 0	3 8	3 6	3 5	4 0	3 8	3 6	3 4	3 8	3 7	3 5	3 4	3 7	3 6	3 4	3 3	3 2					
H m	0 . 9 6 H m	0 . 9 6 H m	4 . 0	4 2	4 0	3 8	3 7	4 1	3 9	3 8	3 7	4 0	3 8	3 7	3 6	3 8	3 7	3 6	3 5	3 4					
			5 . 0	4 2	4 1	4 0	3 8	4 2	4 0	3 9	3 8	4 0	3 9	3 8	3 7	3 9	3 8	3 7	3 6	3 5					
			7 . 0	4 3	4 2	4 1	4 0	4 3	4 2	4 1	4 0	4 1	4 0	4 0	3 9	4 0	3 9	3 9	3 8	3 7					
			1 0 . 0	4 4	4 3	4 2	4 2	4 3	4 3	4 2	4 1	4 2	4 1	4 1	4 0	4 1	4 0	4 0	3 9	3 8					

