

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 2
光源	L L D 3 0 2 0 M L C E 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 5 6 6 3 (1) D R 1
B Z 分類	B Z 1

器具効率		7 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		7 7 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束																						
保守率		良 中 否	0 . 6	6 8	6 4	6 1	5 9	6 7	6 3	6 1	5 9	6 6	6 3	6 1	5 9	6 5	6 3	6 1	5 9	5 9		
			0 . 8	7 1	6 8	6 6	6 4	7 1	6 8	6 6	6 4	7 0	6 7	6 5	6 4	6 9	6 7	6 5	6 4	6 3		
			1 . 0	7 4	7 1	6 9	6 7	7 3	7 0	6 8	6 7	7 2	7 0	6 8	6 6	7 1	6 9	6 7	6 6	6 5		
			0 . 5 6	1 . 2 5	7 6	7 3	7 1	6 9	7 5	7 3	7 1	6 9	7 4	7 2	7 0	6 9	7 3	7 1	7 0	6 8	6 7	
下方投影面積		c m ²	1 . 5	7 7	7 5	7 3	7 1	7 6	7 4	7 2	7 1	7 5	7 3	7 2	7 0	7 4	7 2	7 1	7 0	6 9		
			等価発光面積		c m ²	2 . 0	7 8	7 7	7 5	7 4	7 8	7 6	7 5	7 3	7 6	7 5	7 4	7 3	7 5	7 4	7 3	7 2
取付 高さ	器具間隔最大限					2 . 5	7 9	7 8	7 6	7 5	7 9	7 7	7 6	7 5	7 7	7 6	7 5	7 4	7 6	7 5	7 4	7 3
	横方向 (A)		縦方向 (B)		3 . 0	8 0	7 9	7 7	7 6	7 9	7 8	7 7	7 6	7 8	7 7	7 6	7 5	7 6	7 5	7 5	7 4	7 3
H m	0 . 4 4 H m	0 . 4 4 H m	4 . 0	8 1	8 0	7 9	7 8	8 0	7 9	7 8	7 7	7 8	7 8	7 7	7 6	7 7	7 6	7 6	7 5	7 3		
			5 . 0	8 1	8 0	7 9	7 9	8 0	8 0	7 9	7 8	7 9	7 8	7 8	7 7	7 7	7 7	7 6	7 6	7 4		
			7 . 0	8 2	8 1	8 0	8 0	8 1	8 0	8 0	7 9	7 9	7 9	7 8	7 8	7 8	7 7	7 7	7 7	7 5		
			1 0 . 0	8 2	8 2	8 1	8 1	8 1	8 1	8 0	8 0	8 0	7 9	7 9	7 9	7 8	7 8	7 7	7 7	7 5		

