

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 2
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 l m
管理番号	K 0 1 8 4 6 4 7 (0) D R 1
B Z 分類	B Z 1

器具効率		6 8 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束				6 8 %																		
保守率		良	0 . 6 7	0 . 6	5 7	5 3	5 0	4 8	5 6	5 3	5 0	4 8	5 6	5 2	5 0	4 8	5 5	5 2	5 0	4 8	4 8	
		中	0 . 6 3	0 . 8	6 1	5 8	5 5	5 3	6 1	5 7	5 5	5 3	6 0	5 7	5 5	5 3	5 9	5 6	5 4	5 3	5 2	
		否	0 . 5 6	1 . 0	6 4	6 1	5 8	5 7	6 3	6 0	5 8	5 6	6 2	5 9	5 8	5 6	6 1	5 9	5 7	5 6	5 5	
				1 . 2 5	6 6	6 3	6 1	5 9	6 5	6 3	6 1	5 9	6 4	6 2	6 0	5 9	6 3	6 1	6 0	5 8	5 8	
下方投影面積		c m ²		1 . 5	6 7	6 5	6 3	6 1	6 6	6 4	6 2	6 1	6 5	6 3	6 2	6 1	6 4	6 2	6 1	6 0	5 9	
等価発光面積		c m ²		2 . 0	6 9	6 7	6 5	6 4	6 8	6 6	6 5	6 3	6 7	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 1	
取付 高さ	器具間隔最大限		2 . 5	7 0	6 8	6 7	6 5	6 9	6 7	6 6	6 5	6 8	6 6	6 5	6 4	6 6	6 5	6 4	6 4	6 2		
	横方向 (A) 縦方向 (B)		3 . 0	7 0	6 9	6 8	6 6	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 3		
H m	0 . 7 2 H m	0 . 7 2 H m	4 . 0	7 1	7 0	6 9	6 8	7 0	6 9	6 8	6 8	6 9	6 8	6 7	6 7	6 8	6 7	6 6	6 6	6 4		
			5 . 0	7 1	7 1	7 0	6 9	7 1	7 0	6 9	6 8	6 9	6 9	6 8	6 7	6 8	6 7	6 7	6 6	6 5		
			7 . 0	7 2	7 1	7 1	7 0	7 1	7 1	7 0	6 9	7 0	6 9	6 9	6 8	6 8	6 8	6 8	6 7	6 6		
			1 0 . 0	7 2	7 2	7 1	7 1	7 2	7 1	7 1	7 0	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 8	6 6		

