

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 7 8
光源	L L D 2 0 0 0 M L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 7 5 1 (2) D R 1
B Z 分類	B Z 2

器具効率		6 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 3	3 7	3 4	3 1	4 2	3 7	3 4	3 1	4 1	3 6	3 3	3 1	4 0	3 6	3 3	3 1	3 0
			0 . 6 3	0 . 8	4 8	4 3	4 0	3 7	4 7	4 3	3 9	3 7	4 6	4 2	3 9	3 7	4 4	4 1	3 8	3 6	3 5
			1 . 0	1 . 0	5 2	4 7	4 4	4 1	5 1	4 6	4 3	4 1	4 9	4 5	4 3	4 0	4 8	4 4	4 2	4 0	3 9
			0 . 5 6	1 . 2 5	5 4	5 0	4 7	4 5	5 4	5 0	4 7	4 4	5 2	4 9	4 6	4 4	5 0	4 7	4 5	4 3	4 2
下方投影面積		c m ²	1 . 5	5 6	5 3	5 0	4 7	5 5	5 2	4 9	4 7	5 4	5 1	4 8	4 6	5 2	4 9	4 7	4 6	4 4	
			2 . 0	5 9	5 6	5 3	5 1	5 8	5 5	5 3	5 1	5 6	5 4	5 2	5 0	5 4	5 2	5 1	4 9	4 7	
等価発光面積		c m ²	2 . 5	6 0	5 8	5 6	5 4	5 9	5 7	5 5	5 3	5 7	5 5	5 4	5 2	5 6	5 4	5 3	5 1	5 0	
			3 . 0	6 1	5 9	5 7	5 5	6 0	5 8	5 7	5 5	5 9	5 7	5 5	5 4	5 7	5 5	5 4	5 3	5 1	
H m	1 . 2 4 H m	1 . 2 4 H m	4 . 0	6 3	6 1	5 9	5 8	6 2	6 0	5 9	5 7	6 0	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 3	
			5 . 0	6 3	6 2	6 1	5 9	6 2	6 1	6 0	5 9	6 1	5 9	5 8	5 8	5 9	5 8	5 7	5 6	5 4	
			7 . 0	6 4	6 3	6 2	6 1	6 3	6 2	6 1	6 1	6 2	6 1	6 0	5 9	6 0	5 9	5 8	5 8	5 6	
			1 0 . 0	6 5	6 4	6 4	6 3	6 4	6 3	6 3	6 2	6 2	6 2	6 1	6 1	6 0	6 0	5 9	5 9	5 7	

