

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 3 3
光源	L L D 2 0 0 0 C U 1 × 1 5 6 6 . 0 l m
管理番号	K 0 1 7 9 0 7 7 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 1 . 8 / B Z 5

器具効率		9 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1)															
保守率		良 中 否	0 . 6 7	0 . 6	5 4	4 3	3 6	3 1	5 3	4 2	3 6	3 1	5 0	4 1	3 5	3 0	4 7	3 9	3 4	3 0	2 8	
			0 . 6 3	0 . 8	6 4	5 3	4 6	4 1	6 2	5 2	4 5	4 0	5 9	5 0	4 4	4 0	5 6	4 8	4 3	3 9	3 6	
			0 . 5 6	1 . 0	7 0	6 0	5 3	4 8	6 8	5 9	5 2	4 7	6 4	5 7	5 1	4 6	6 1	5 5	4 9	4 5	4 3	
				1 . 2 5	7 5	6 6	6 0	5 4	7 3	6 5	5 9	5 4	7 0	6 3	5 7	5 3	6 6	6 0	5 5	5 2	4 9	
下方投影面積		c m ²	1 . 5	7 9	7 1	6 5	5 9	7 7	6 9	6 4	5 9	7 3	6 7	6 2	5 7	6 9	6 4	6 0	5 6	5 3		
			等価発光面積	c m ²	2 . 0	8 4	7 7	7 1	6 7	8 2	7 6	7 0	6 6	7 8	7 3	6 8	6 4	7 4	7 0	6 6	6 3	5 9
取付 高さ	器具間隔最大限		2 . 5	8 7	8 1	7 6	7 2	8 5	8 0	7 5	7 1	8 1	7 6	7 2	6 9	7 7	7 3	7 0	6 7	6 3		
	横方向 (A)	縦方向 (B)	3 . 0	8 9	8 4	8 0	7 6	8 7	8 2	7 8	7 5	8 3	7 9	7 6	7 2	7 9	7 6	7 3	7 0	6 7		
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	9 2	8 8	8 4	8 1	9 0	8 6	8 3	8 0	8 6	8 3	8 0	7 7	8 2	8 0	7 7	7 5	7 1		
			5 . 0	9 4	9 0	8 7	8 4	9 2	8 9	8 6	8 3	8 8	8 5	8 3	8 0	8 4	8 2	8 0	7 8	7 4		
			7 . 0	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 7	9 0	8 8	8 6	8 4	8 6	8 5	8 3	8 1	7 7		
			1 0 . 0	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 0	9 2	9 0	8 9	8 7	8 8	8 7	8 6	8 4	8 0		

