

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 3 3
光源	LLD5000LCC1 ×1 1140.0 l m
管理番号	K0190443 (0) DR 1
B Z 分類	B Z 3

器具効率		96 %		反射率	天井	80 %				70 %				50 %				30 %				0 %	
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %	
					室指数	照明率 (X0.01)																	
保守率		良 中 否	0.67	0.6	62	52	45	41	60	51	45	41	58	50	44	40	56	49	44	40	39		
			0.63	0.8	71	62	56	52	70	62	56	51	68	60	55	51	66	59	54	51	49		
			0.56	1.0	77	69	63	59	76	68	63	59	74	67	62	58	71	66	61	58	56		
				1.25	82	75	70	66	81	74	69	65	79	73	68	65	76	71	67	64	62		
下方投影面積		c m ²		1.5	86	79	74	70	84	78	74	70	82	77	73	69	79	75	72	69	67		
			等価発光面積	c m ²	2.0	90	85	81	77	89	84	80	77	86	82	79	76	84	80	77	75	73	
取付 高さ	器具間隔最大限			2.5	93	88	85	82	91	87	84	81	89	85	82	80	86	84	81	79	76		
	横方向 (A)		縦方向 (B)	3.0	95	91	87	85	93	90	87	84	91	88	85	83	88	86	84	82	79		
H m	1.26 H m		1.26 H m	4.0	97	94	91	89	95	93	90	88	93	91	89	87	90	89	87	85	83		
				5.0	98	96	93	91	97	95	92	91	94	92	91	89	92	90	89	88	85		
				7.0	100	98	96	95	98	97	95	94	96	94	93	92	93	92	91	90	87		
				10.0	101	99	98	97	99	98	97	96	97	96	95	94	95	94	93	92	89		

