

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | L G B 1 6 1 4 1         |
| 光源       | LLD2000LCT1 ×1 531.0 lm |
| 管理番号     | K0190527 ( 0 ) DR 1     |
| B Z 分類   | B Z 3                   |

| 器具効率         |                     | 64 %            | 反射率  | 天井                | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------------|---------------------|-----------------|------|-------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|              |                     |                 |      | 壁                 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|              |                     |                 |      | 床                 | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
| 上方光束<br>下方光束 |                     | 1 %<br>63 %     | 室指数  | 照明率 ( X0.01 ) ZCM |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率          |                     | 良<br>中<br>否     | 0.67 | 0.6               | 40   | 33 | 28 | 25 | 39   | 32 | 28 | 25 | 38   | 32 | 28 | 25 | 36   | 31 | 28 | 25 | 24  |
|              |                     |                 | 0.63 | 0.8               | 46   | 40 | 36 | 33 | 46   | 40 | 36 | 33 | 44   | 39 | 35 | 32 | 42   | 38 | 35 | 32 | 31  |
|              |                     |                 | 1.0  | 51                | 45   | 41 | 38 | 50 | 44   | 40 | 38 | 48 | 43   | 40 | 37 | 46 | 42   | 39 | 37 | 36 |     |
|              |                     |                 | 0.56 | 1.25              | 54   | 49 | 45 | 42 | 53   | 48 | 45 | 42 | 51   | 47 | 44 | 42 | 50   | 46 | 43 | 41 | 40  |
| 下方投影面積       |                     | cm <sup>2</sup> | 1.5  | 56                | 52   | 48 | 45 | 55 | 51   | 48 | 45 | 53 | 50   | 47 | 45 | 52 | 49   | 46 | 44 | 43 |     |
| 等価発光面積       |                     | cm <sup>2</sup> | 2.0  | 59                | 56   | 52 | 50 | 58 | 55   | 52 | 50 | 56 | 53   | 51 | 49 | 55 | 52   | 50 | 48 | 47 |     |
| 取付<br>高さ     | 器具間隔最大限             |                 | 2.5  | 61                | 58   | 55 | 53 | 60 | 57   | 55 | 53 | 58 | 56   | 54 | 52 | 57 | 54   | 53 | 51 | 49 |     |
|              | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0  | 62                | 60   | 57 | 55 | 61 | 59   | 57 | 55 | 60 | 57   | 55 | 54 | 58 | 56   | 54 | 53 | 51 |     |
| H m          | 1.25 H m            | 1.25 H m        | 4.0  | 64                | 62   | 60 | 58 | 63 | 61   | 59 | 58 | 61 | 59   | 58 | 57 | 59 | 58   | 57 | 56 | 54 |     |
|              |                     |                 | 5.0  | 65                | 63   | 61 | 60 | 64 | 62   | 61 | 59 | 62 | 61   | 59 | 58 | 60 | 59   | 58 | 57 | 55 |     |
|              |                     |                 | 7.0  | 66                | 65   | 63 | 62 | 65 | 64   | 63 | 62 | 63 | 62   | 61 | 60 | 62 | 61   | 60 | 59 | 57 |     |
|              |                     |                 | 10.0 | 67                | 66   | 65 | 64 | 66 | 65   | 64 | 63 | 64 | 63   | 63 | 62 | 63 | 62   | 61 | 61 | 59 |     |

