

屋内照明器具特性	
品番 (品名)	LGB15116
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0179070 (0) DR 1
BZ分類	BZ1

器具効率		96 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		96 %																							
保守率		良 中 否	0.67	0.6	82	77	73	71	82	77	73	71	80	76	73	71	79	75	73	71	70				
			0.63	0.8	87	82	79	77	87	82	79	77	85	81	78	76	84	81	78	76	75				
			0.56	1.0	90	86	83	80	90	86	83	80	88	85	82	80	87	84	81	80	78				
				1.25	93	89	86	84	92	89	86	84	91	87	85	83	89	86	84	83	81				
下方投影面積		c m ²		1.5	95	91	89	86	94	91	88	86	92	89	87	85	91	88	86	85	83				
等価発光面積			c m ²	2.0	97	94	92	90	96	94	91	90	94	92	90	89	93	91	89	88	86				
取付 高さ	器具間隔最大限			2.5	99	96	94	92	98	95	93	92	96	94	92	91	94	92	91	90	88				
	横方向 (A)	縦方向 (B)		3.0	99	97	96	94	98	97	95	93	96	95	93	92	95	93	92	91	89				
H m	0.37 H m	0.37 H m		4.0	101	99	98	96	100	98	97	96	98	96	95	94	96	95	94	93	91				
				5.0	101	100	99	98	100	99	98	97	98	97	96	95	96	95	95	94	92				
				7.0	102	101	100	99	101	100	99	98	99	98	98	97	97	96	96	95	93				
				10.0	103	102	101	100	102	101	100	100	100	99	98	98	98	97	97	96	94				

