

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 8
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 3 2 1 (0) D R 1
B Z 分類	B Z 3

器具効率		6 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 7	3 3	3 0	4 3	3 7	3 3	3 0	4 2	3 6	3 3	3 0	4 1	3 6	3 2	3 0	2 9	
			0 . 6 3	0 . 8	5 0	4 4	3 9	3 6	4 9	4 3	3 9	3 6	4 8	4 2	3 9	3 6	4 6	4 2	3 8	3 6	3 5	
			0 . 5 6	1 . 0	5 4	4 8	4 4	4 1	5 3	4 8	4 4	4 0	5 1	4 7	4 3	4 0	5 0	4 6	4 2	4 0	3 9	
				1 . 2 5	5 7	5 2	4 8	4 5	5 6	5 1	4 8	4 5	5 5	5 0	4 7	4 4	5 3	4 9	4 6	4 4	4 3	
下方投影面積		c m ²	1 . 5	6 0	5 5	5 1	4 8	5 9	5 4	5 1	4 8	5 7	5 3	5 0	4 7	5 5	5 2	4 9	4 7	4 6		
			等価発光面積	2 . 0	6 3	5 9	5 5	5 3	6 2	5 8	5 5	5 2	6 0	5 7	5 4	5 2	5 8	5 6	5 3	5 1	5 0	
取付 高さ	器具間隔最大限		2 . 5	6 5	6 1	5 8	5 6	6 4	6 0	5 8	5 5	6 2	5 9	5 7	5 5	6 0	5 8	5 6	5 4	5 3		
	横方向 (A)	縦方向 (B)	3 . 0	6 6	6 3	6 0	5 8	6 5	6 2	6 0	5 8	6 3	6 1	5 9	5 7	6 1	6 0	5 8	5 6	5 5		
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	6 8	6 5	6 3	6 1	6 7	6 5	6 3	6 1	6 5	6 3	6 1	6 0	6 3	6 2	6 0	5 9	5 7		
			5 . 0	6 9	6 7	6 5	6 3	6 8	6 6	6 4	6 3	6 6	6 5	6 3	6 2	6 4	6 3	6 2	6 1	5 9		
			7 . 0	7 0	6 8	6 7	6 6	6 9	6 8	6 6	6 5	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 1		
			1 0 . 0	7 1	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 8	6 7	6 7	6 6	6 7	6 6	6 5	6 5	6 3		

