

屋内照明器具特性	
品番 (品名)	LGB16121
光源	LLD5000LCC1 ×1 1140.0 lm
管理番号	K0190440 (0) DR 1
BZ分類	BZ3

器具効率		97 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	62	52	46	41	61	51	45	41	59	51	45	41	57	50	44	41	39				
			0.63	0.8	72	63	56	52	71	62	56	52	68	61	56	52	66	60	55	51	50				
			0.56	1.0	78	70	64	59	77	69	63	59	74	68	63	59	72	66	62	59	57				
				1.25	83	76	70	66	82	75	70	66	79	74	69	65	77	72	68	65	63				
下方投影面積		cm ²		1.5	87	80	75	71	85	79	74	71	83	78	73	70	80	76	72	69	67				
			等価発光面積	cm ²	2.0	91	86	81	78	90	85	81	77	87	83	79	76	85	81	78	76	74			
取付 高さ	器具間隔最大限			2.5	94	89	85	82	92	88	85	82	90	86	83	81	88	85	82	80	77				
	横方向 (A) 縦方向 (B)			3.0	95	92	88	85	94	91	87	85	92	89	86	84	89	87	85	83	80				
H m	1.26 H m 1.26 H m			4.0	98	95	92	89	96	94	91	89	94	92	89	88	92	90	88	86	84				
				5.0	99	97	94	92	98	96	93	91	95	93	92	90	93	92	90	89	86				
				7.0	101	99	97	95	99	98	96	95	97	96	94	93	95	94	93	91	89				
				10.0	102	100	99	98	101	99	98	97	98	97	96	95	96	95	94	94	91				

