

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 5
光源	L L D 4 0 0 0 L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 2 9 9 (0) D R 1
B Z 分類	B Z 2

器具効率		53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	3 5	3 0	2 7	2 4	3 5	3 0	2 7	2 4	3 4	2 9	2 6	2 4	3 3	2 9	2 6	2 4	2 3
			0 . 6 3	0 . 8	4 1	3 6	3 3	3 1	4 0	3 6	3 3	3 1	3 9	3 5	3 3	3 1	3 8	3 5	3 2	3 0	3 0
			0 . 5 6	1 . 0	4 4	4 0	3 7	3 5	4 4	4 0	3 7	3 5	4 2	3 9	3 7	3 5	4 1	3 8	3 6	3 5	3 4
				1 . 2 5	4 7	4 3	4 1	3 9	4 6	4 3	4 0	3 8	4 5	4 2	4 0	3 8	4 4	4 1	4 0	3 8	3 7
下方投影面積		c m ²	1 . 5	4 9	4 6	4 3	4 1	4 8	4 5	4 3	4 1	4 7	4 4	4 2	4 1	4 6	4 3	4 2	4 0	3 9	
			等価発光面積	c m ²	2 . 0	5 1	4 8	4 6	4 4	5 0	4 8	4 6	4 4	4 9	4 7	4 5	4 4	4 8	4 6	4 5	4 3
取付 高さ	器具間隔最大限		2 . 5	5 2	5 0	4 8	4 7	5 2	5 0	4 8	4 6	5 0	4 9	4 7	4 6	4 9	4 8	4 6	4 5	4 4	
	横方向 (A) 縦方向 (B)		3 . 0	5 3	5 1	5 0	4 8	5 2	5 1	4 9	4 8	5 1	5 0	4 8	4 7	5 0	4 9	4 8	4 7	4 5	
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	5 4	5 3	5 1	5 0	5 4	5 2	5 1	5 0	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 9	4 7	
			5 . 0	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 2	5 1	5 0	5 0	4 8	
			7 . 0	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 3	5 4	5 3	5 2	5 2	5 3	5 2	5 1	5 1	5 0	
			1 0 . 0	5 6	5 6	5 5	5 4	5 6	5 5	5 4	5 4	5 4	5 4	5 3	5 3	5 3	5 3	5 2	5 2	5 0	

