

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 5
光源	L L D 4 0 4 0 2 C Q 1 (K A K U S A N) × 1 8 6 0 . 0 1 m
管理番号	K 0 1 8 4 4 8 6 (0) D R 1
B Z 分類	B Z 2 / 0 . 9 / B Z 1 / 4 . 5 / B Z 2 / 6 . 0 / B Z 1

器具効率		4 5 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		4 5 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	3 1	2 7	2 5	2 3	3 1	2 7	2 5	2 3	3 0	2 7	2 4	2 3	2 9	2 6	2 4	2 3	2 2				
			0 . 6 3	0 . 8	3 6	3 2	3 0	2 8	3 5	3 2	3 0	2 8	3 5	3 2	2 9	2 8	3 4	3 1	2 9	2 8	2 7				
			1 . 0	3 9	3 6	3 3	3 1	3 8	3 5	3 3	3 1	3 7	3 5	3 3	3 1	3 6	3 4	3 2	3 1	3 0					
			0 . 5 6	1 . 2 5	4 1	3 8	3 6	3 4	4 0	3 8	3 6	3 4	3 9	3 7	3 5	3 4	3 8	3 7	3 5	3 4	3 3				
下方投影面積 等価発光面積		c m ²	1 . 5	4 2	4 0	3 8	3 6	4 2	3 9	3 8	3 6	4 1	3 9	3 7	3 6	4 0	3 8	3 7	3 6	3 5					
			2 . 0	4 4	4 2	4 0	3 9	4 3	4 2	4 0	3 9	4 2	4 1	4 0	3 8	4 1	4 0	3 9	3 8	3 7					
取付 高さ	器具間隔最大限		2 . 5	4 5	4 3	4 2	4 1	4 4	4 3	4 2	4 1	4 3	4 2	4 1	4 0	4 2	4 1	4 0	4 0	3 9					
	横方向 (A) 縦方向 (B)		3 . 0	4 6	4 4	4 3	4 2	4 5	4 4	4 3	4 2	4 4	4 3	4 2	4 1	4 3	4 2	4 1	4 1	4 0					
H m	1 . 2 6 H m	1 . 2 6 H m	4 . 0	4 7	4 5	4 4	4 4	4 6	4 5	4 4	4 3	4 5	4 4	4 3	4 3	4 4	4 3	4 3	4 2	4 1					
			5 . 0	4 7	4 6	4 5	4 5	4 6	4 6	4 5	4 4	4 5	4 5	4 4	4 4	4 4	4 4	4 3	4 3	4 2					
			7 . 0	4 8	4 7	4 6	4 6	4 7	4 6	4 6	4 5	4 6	4 5	4 5	4 5	4 5	4 5	4 4	4 4	4 3					
			1 0 . 0	4 8	4 8	4 7	4 7	4 7	4 7	4 7	4 6	4 6	4 6	4 6	4 5	4 5	4 5	4 5	4 5	4 3					

