

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 9
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 3 0 2 (0) D R 1
B Z 分類	B Z 2

器具効率		5 6 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		5 6 %																							
保守率		良 中 否	0 . 6 7	0 . 6	3 7	3 1	2 8	2 6	3 6	3 1	2 8	2 5	3 5	3 1	2 8	2 5	3 4	3 0	2 7	2 5	2 4				
			0 . 6 3	0 . 8	4 3	3 8	3 5	3 2	4 2	3 8	3 4	3 2	4 1	3 7	3 4	3 2	4 0	3 6	3 4	3 2	3 1				
			0 . 5 6	1 . 0	4 6	4 2	3 9	3 7	4 6	4 2	3 9	3 6	4 4	4 1	3 8	3 6	4 3	4 0	3 8	3 6	3 5				
				1 . 2 5	4 9	4 5	4 3	4 0	4 8	4 5	4 2	4 0	4 7	4 4	4 2	4 0	4 6	4 3	4 1	4 0	3 9				
下方投影面積		c m ²	1 . 5	5 1	4 8	4 5	4 3	5 0	4 7	4 5	4 3	4 9	4 6	4 4	4 2	4 8	4 5	4 4	4 2	4 1					
等価発光面積			c m ²	2 . 0	5 3	5 1	4 8	4 6	5 3	5 0	4 8	4 6	5 1	4 9	4 7	4 6	5 0	4 8	4 7	4 5	4 4				
取付高さ	器具間隔最大限		2 . 5	5 5	5 2	5 0	4 9	5 4	5 2	5 0	4 8	5 3	5 1	4 9	4 8	5 1	5 0	4 9	4 7	4 6					
	横方向 (A) 縦方向 (B)		3 . 0	5 6	5 4	5 2	5 0	5 5	5 3	5 1	5 0	5 3	5 2	5 1	4 9	5 2	5 1	5 0	4 9	4 8					
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	5 7	5 5	5 4	5 3	5 6	5 5	5 3	5 2	5 5	5 3	5 2	5 1	5 3	5 2	5 2	5 1	4 9					
			5 . 0	5 7	5 6	5 5	5 4	5 7	5 6	5 4	5 4	5 5	5 4	5 3	5 3	5 4	5 3	5 3	5 2	5 0					
			7 . 0	5 8	5 7	5 6	5 6	5 7	5 7	5 6	5 5	5 6	5 5	5 5	5 4	5 5	5 4	5 4	5 3	5 2					
			1 0 . 0	5 9	5 8	5 7	5 7	5 8	5 7	5 7	5 6	5 7	5 6	5 6	5 5	5 5	5 5	5 5	5 4	5 3					

