

屋内照明器具特性	
品番 (品名)	XLGB1518
光源	LLD40005CQ1 ×1 845.0 lm
管理番号	K0175669 (1) DR1
BZ分類	BZ2

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	42	36	33	30	41	36	33	30	40	35	32	30	39	35	32	30	29
			0.63	0.8	47	42	38	36	46	41	38	36	45	41	38	36	43	40	37	35	34
			0.56	1.0	50	46	42	40	49	45	42	40	48	44	41	39	46	43	41	39	38
				1.25	53	49	46	43	52	48	45	43	50	47	45	43	49	46	44	42	41
下方投影面積		cm ²	1.5	55	51	48	46	54	51	48	46	52	49	47	45	51	48	46	45	43	
			2.0	57	54	52	50	56	54	51	49	55	52	50	49	53	51	49	48	46	
等価発光面積		cm ²	2.5	59	56	54	52	58	55	53	52	56	54	52	51	54	53	51	50	48	
			3.0	60	58	56	54	59	57	55	53	57	55	54	53	55	54	53	52	50	
H _m	1.23H _m	1.23H _m	4.0	61	59	58	56	60	58	57	56	58	57	56	55	57	56	55	54	52	
			5.0	62	60	59	58	61	60	58	57	59	58	57	56	57	57	56	55	53	
			7.0	63	62	61	60	62	61	60	59	60	59	58	58	58	58	57	56	54	
			10.0	63	63	62	61	62	62	61	60	61	60	60	59	59	58	58	58	55	

