

屋内照明器具特性	
品番 (品名)	L G B 5 8 1 0 0
光源	L L D 3 0 2 0 C U 1 × 1 6 1 5 . 0 l m
管理番号	K 0 1 7 9 1 1 7 (0) D R 1
B Z 分類	B Z 1

器具効率			8 6 %		反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
						壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
						床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束			0 %		室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束			8 6 %																					
保守率			良 中 否	0 . 6 7	0 . 6	7 2	6 6	6 3	6 0	7 1	6 6	6 3	6 0	7 0	6 5	6 2	6 0	6 9	6 5	6 2	6 0	5 9		
				0 . 6 3	0 . 8	7 6	7 2	6 8	6 6	7 6	7 1	6 8	6 6	7 4	7 0	6 8	6 5	7 3	7 0	6 7	6 5	6 4		
				0 . 5 6	1 . 0	8 0	7 5	7 2	6 9	7 9	7 5	7 2	6 9	7 7	7 4	7 1	6 9	7 6	7 3	7 1	6 9	6 8		
				1 . 2 5	8 2	7 8	7 5	7 3	8 1	7 8	7 5	7 3	8 0	7 7	7 4	7 2	7 8	7 6	7 4	7 2	7 1			
下方投影面積			c m ²	1 . 5	8 4	8 0	7 8	7 5	8 3	8 0	7 7	7 5	8 1	7 9	7 6	7 5	8 0	7 8	7 6	7 4	7 3			
				2 . 0	8 6	8 3	8 1	7 9	8 5	8 3	8 0	7 9	8 4	8 1	7 9	7 8	8 2	8 0	7 8	7 7	7 6			
取付 高さ	器具間隔最大限			2 . 5	8 8	8 5	8 3	8 1	8 7	8 4	8 2	8 1	8 5	8 3	8 1	8 0	8 3	8 2	8 0	7 9	7 7			
	横方向 (A)		縦方向 (B)	3 . 0	8 9	8 6	8 5	8 3	8 8	8 6	8 4	8 2	8 6	8 4	8 3	8 1	8 4	8 3	8 2	8 0	7 9			
H m	0 . 3 3 H m		0 . 3 3 H m	4 . 0	9 0	8 8	8 7	8 5	8 9	8 7	8 6	8 5	8 7	8 6	8 5	8 3	8 5	8 4	8 3	8 2	8 0			
				5 . 0	9 0	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 1			
				7 . 0	9 1	9 0	8 9	8 8	9 0	8 9	8 9	8 8	8 8	8 8	8 7	8 6	8 7	8 6	8 5	8 5	8 3			
				1 0 . 0	9 2	9 1	9 0	9 0	9 1	9 0	9 0	8 9	8 9	8 8	8 8	8 7	8 7	8 7	8 6	8 6	8 4			

