

屋内照明器具特性	
品番 (品名)	L G W4 1 0 0 0
光源	L L D4 0 0 0 1 C Q1 ×1 845.0 l m
管理番号	K0176343 (0) D R 1
B Z 分類	B Z 3 / 0.9 / B Z 2 / 4.5 / B Z 3 / 6.0 / B Z 2

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.63	0.6	37	31	28	25	37	31	27	25	36	31	27	25	35	30	27	25	24
			0.6	0.8	43	38	34	32	43	38	34	32	41	37	34	31	40	36	33	31	30
				1.0	47	42	39	36	46	42	39	36	45	41	38	36	44	40	38	36	35
			0.56	1.25	50	46	43	40	50	46	43	40	48	45	42	40	47	44	42	40	39
下方投影面積		c m ²		1.5	52	49	46	43	52	48	45	43	50	47	45	43	49	46	44	42	41
			等価発光面積	c m ²	2.0	55	52	49	47	54	51	49	47	53	50	48	47	51	49	48	46
取付 高さ	器具間隔最大限			2.5	56	54	52	50	56	53	51	50	54	52	51	49	53	51	50	48	47
	横方向 (A) 縦方向 (B)			3.0	58	55	53	52	57	55	53	51	55	54	52	51	54	53	51	50	49
H m	1.17 H m	1.17 H m		4.0	59	57	56	54	58	57	55	54	57	55	54	53	55	54	53	52	51
				5.0	60	58	57	56	59	58	56	55	57	56	55	54	56	55	54	54	52
				7.0	60	59	58	58	60	59	58	57	58	58	57	56	57	56	56	55	54
				10.0	61	60	60	59	60	60	59	58	59	58	58	57	58	57	57	56	55

