

屋内照明器具特性	
品番 (品名)	XLGE1022
光源	LLD2020VCE1 ×1 460.0 lm
管理番号	K0176348 (0) DR1
BZ分類	BZ1

器具効率		91 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		91 %																						
保守率		良 中 否	0.63	0.6	77	72	69	66	77	72	69	66	76	71	68	66	75	71	68	66	65			
			0.6	0.8	83	78	75	72	82	78	75	72	81	77	74	72	79	76	74	72	71			
				1.0	86	82	79	76	85	81	78	76	84	80	78	76	82	79	77	76	74			
			0.56	1.25	89	85	82	80	88	84	82	80	86	83	81	79	85	82	80	79	77			
下方投影面積		c m ²		1.5	90	87	84	82	89	86	84	82	88	85	83	82	86	84	82	81	80			
				2.0	92	90	88	86	92	89	87	85	90	88	86	85	88	87	85	84	82			
取付 高さ	器具間隔最大限			2.5	94	92	90	88	93	91	89	88	91	89	88	87	89	88	87	86	84			
	横方向 (A)		縦方向 (B)		3.0	95	93	91	90	94	92	90	89	92	90	89	88	90	89	88	87	85		
H m	0.41 H m		0.41 H m		4.0	96	94	93	92	95	93	92	91	93	92	91	90	91	90	89	86			
					5.0	96	95	94	93	95	94	93	92	93	92	92	91	92	91	90	87			
					7.0	97	96	95	94	96	95	94	94	94	93	93	92	92	92	91	88			
					10.0	98	97	96	96	97	96	95	95	95	94	94	93	93	92	92	89			

