

屋内照明器具特性	
品番 (品名)	LGB57660K
光源	LDA7L-D-G/S/Z6 ×6 810.0 lm
管理番号	K0165036(0)D 1
BZ分類	BZ8/0.7/BZ7

器具効率		9 4 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		3 1 % 6 3 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 2	2 4	1 9	4 1	3 0	2 3	1 8	3 6	2 7	2 0	1 6	3 1	2 3	1 8	1 4	1 0				
			0 . 6 3	0 . 8	5 2	4 0	3 2	2 6	4 8	3 8	3 0	2 5	4 2	3 3	2 7	2 2	3 6	2 9	2 4	2 0	1 5				
			1 . 0	5 7	4 6	3 8	3 1	5 4	4 3	3 6	3 0	4 7	3 8	3 2	2 7	4 0	3 3	2 8	2 4	1 8					
			0 . 5 6	1 . 2 5	6 3	5 2	4 4	3 7	5 9	4 9	4 1	3 6	5 1	4 3	3 7	3 2	4 4	3 8	3 3	2 9	2 2				
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	6 6	5 6	4 9	4 2	6 2	5 3	4 6	4 0	5 4	4 7	4 1	3 6	4 7	4 1	3 6	3 2	2 5					
			2 . 0	7 2	6 3	5 6	5 0	6 8	6 0	5 3	4 7	5 9	5 3	4 7	4 3	5 2	4 7	4 2	3 8	3 0					
取付 高さ	器具間隔最大限		2 . 5	7 5	6 8	6 1	5 5	7 1	6 4	5 8	5 3	6 3	5 7	5 2	4 8	5 5	5 0	4 6	4 3	3 4					
	横方向 (A)	縦方向 (B)	3 . 0	7 8	7 1	6 5	6 0	7 4	6 7	6 2	5 7	6 5	6 0	5 5	5 1	5 7	5 3	4 9	4 6	3 7					
H m	1 . 4 1 H m	1 . 4 1 H m	4 . 0	8 2	7 6	7 1	6 6	7 7	7 2	6 7	6 3	6 8	6 4	6 0	5 7	6 0	5 7	5 4	5 1	4 1					
			5 . 0	8 4	7 9	7 4	7 0	7 9	7 5	7 1	6 7	7 1	6 7	6 3	6 0	6 2	5 9	5 7	5 4	4 4					
			7 . 0	8 6	8 3	7 9	7 5	8 2	7 8	7 5	7 2	7 3	7 0	6 8	6 5	6 5	6 3	6 0	5 8	4 8					
			1 0 . 0	8 9	8 6	8 3	8 0	8 4	8 1	7 9	7 6	7 5	7 3	7 1	6 9	6 7	6 5	6 4	6 2	5 2					

