

屋内照明器具特性	
品番 (品名)	L G S 3 5 0 5 L
光源	LDA13L - G / Z100E / S / W ×1 1520.0 l m
管理番号	K0172136 (0) DB 1
B Z 分類	BZ6

器具効率		61 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		18 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		43 %																								
保守率		良 中 否	0.67	0.6	30	23	18	15	28	22	17	14	25	20	16	13	22	18	14	12	10					
			0.63	0.8	36	28	23	20	34	27	22	19	30	24	21	18	26	22	19	16	13					
			1.0	39	33	28	24	37	31	26	23	33	28	24	21	29	25	22	20	16						
			0.56	1.25	43	36	32	28	40	35	30	27	36	31	28	25	32	28	25	23	19					
下方投影面積		cm ²	1.5	45	39	35	31	43	37	33	30	38	34	30	28	34	30	28	25	21						
等価発光面積		cm ²	2.0	49	44	39	36	46	41	38	35	41	38	34	32	37	34	31	29	24						
取付 高さ	器具間隔最大限		2.5	51	46	43	39	48	44	41	38	43	40	37	35	39	36	34	32	27						
	横方向 (A)	縦方向 (B)	3.0	52	48	45	42	50	46	43	40	45	42	39	37	40	38	36	34	29						
H m	1.52 H m	1.52 H m	4.0	54	51	48	46	52	49	46	44	47	44	42	40	42	40	38	37	31						
			5.0	56	53	50	48	53	50	48	46	48	46	44	42	43	41	40	39	33						
			7.0	57	55	53	51	54	53	51	49	49	48	46	45	45	43	42	41	35						
			10.0	58	57	55	54	56	54	53	51	51	49	48	47	46	45	44	43	37						

