

屋内照明器具特性	
品番 (品名)	L G W5 6 0 0 9 B U
光源	L D A 5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 3 1 5 5 5 (1) D B 1
B Z 分類	B Z 6

器具効率		3 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 7 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 8 %																					
保守率		良 中 否	0 . 6 3	0 . 6	1 7	1 2	1 0	8	1 5	1 1	9	7	1 3	1 0	8	6	1 0	8	7	5	4		
			0 . 6	0 . 8	2 0	1 6	1 3	1 1	1 8	1 4	1 2	1 0	1 5	1 2	1 0	9	1 2	1 0	9	8	5		
			0 . 5 6	1 . 0	2 2	1 8	1 5	1 3	2 0	1 7	1 4	1 2	1 7	1 4	1 2	1 1	1 4	1 2	1 0	9	6		
				1 . 2 5	2 4	2 0	1 8	1 5	2 2	1 9	1 6	1 5	1 8	1 6	1 4	1 3	1 5	1 3	1 2	1 1	8		
下方投影面積		c m ²	1 . 5	2 5	2 2	1 9	1 7	2 3	2 0	1 8	1 6	1 9	1 7	1 6	1 4	1 6	1 4	1 3	1 2	9			
等価発光面積		c m ²	2 . 0	2 7	2 4	2 2	2 0	2 5	2 2	2 0	1 9	2 1	1 9	1 8	1 6	1 7	1 6	1 5	1 4	1 0			
取付 高さ	器具間隔最大限		2 . 5	2 8	2 6	2 4	2 2	2 6	2 4	2 2	2 1	2 2	2 0	1 9	1 8	1 8	1 7	1 6	1 5	1 1			
	横方向 (A)		縦方向 (B)		3 . 0	2 9	2 7	2 5	2 3	2 7	2 5	2 3	2 2	2 3	2 1	2 0	1 9	1 8	1 7	1 6	1 2		
H m	1 . 4 7 H m	1 . 2 7 H m	4 . 0	3 0	2 8	2 7	2 5	2 8	2 6	2 5	2 4	2 4	2 3	2 2	2 1	2 0	1 9	1 8	1 8	1 3			
			5 . 0	3 1	2 9	2 8	2 7	2 9	2 7	2 6	2 5	2 4	2 3	2 2	2 2	2 0	2 0	1 9	1 8	1 4			
			7 . 0	3 2	3 0	2 9	2 8	2 9	2 8	2 7	2 7	2 5	2 4	2 4	2 3	2 1	2 1	2 0	2 0	1 4			
			1 0 . 0	3 2	3 1	3 1	3 0	3 0	2 9	2 9	2 8	2 6	2 5	2 5	2 4	2 2	2 1	2 1	2 0	1 5			

