

屋内照明器具特性	
品番 (品名)	L G W8 0 3 0 5 K
光源	LED2700_70_348 ×1 348.0 l m
管理番号	K0146953 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		3 3 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		6 7 %																					
保守率		良	0 . 6 3	0 . 6	4 9	3 7	2 9	2 3	4 6	3 5	2 7	2 2	4 0	3 1	2 5	2 0	3 5	2 8	2 2	1 9	1 4		
		中	0 . 6	0 . 8	5 8	4 6	3 8	3 2	5 4	4 4	3 6	3 1	4 8	3 9	3 3	2 8	4 2	3 5	2 9	2 5	2 0		
		否	0 . 5 6	1 . 0	6 4	5 3	4 5	3 9	6 0	5 0	4 3	3 7	5 3	4 5	3 8	3 4	4 6	4 0	3 4	3 0	2 4		
				1 . 2 5	7 0	5 9	5 1	4 5	6 6	5 6	4 9	4 3	5 8	5 0	4 4	3 9	5 0	4 4	4 0	3 6	2 9		
下方投影面積		c m ²		1 . 5	7 4	6 4	5 6	5 0	6 9	6 1	5 4	4 8	6 1	5 4	4 9	4 4	5 4	4 8	4 3	4 0	3 2		
等価発光面積		c m ²		2 . 0	7 9	7 1	6 4	5 8	7 5	6 7	6 1	5 6	6 6	6 0	5 5	5 1	5 8	5 3	4 9	4 6	3 7		
取付高さ	器具間隔最大限			2 . 5	8 3	7 5	6 9	6 4	7 8	7 2	6 6	6 1	6 9	6 4	5 9	5 5	6 1	5 7	5 3	5 0	4 1		
	横方向 (A)		縦方向 (B)	3 . 0	8 5	7 9	7 3	6 8	8 1	7 5	7 0	6 5	7 2	6 7	6 3	5 9	6 3	5 9	5 6	5 3	4 4		
H m	1 . 3 9 H m	1 . 3 9 H m	4 . 0	8 9	8 3	7 8	7 4	8 4	7 9	7 5	7 1	7 5	7 1	6 7	6 4	6 6	6 3	6 0	5 8	4 7			
			5 . 0	9 1	8 6	8 2	7 8	8 6	8 2	7 8	7 5	7 7	7 3	7 0	6 8	6 8	6 5	6 3	6 1	5 0			
			7 . 0	9 3	9 0	8 6	8 3	8 8	8 5	8 2	7 9	7 9	7 7	7 4	7 2	7 0	6 8	6 6	6 5	5 4			
			1 0 . 0	9 5	9 3	9 0	8 8	9 0	8 8	8 6	8 3	8 1	7 9	7 7	7 6	7 2	7 1	6 9	6 8	5 6			

