

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | L G W C 8 1 3 0 7 K         |
| 光源       | LED2700_70_248 ×1 248.0 l m |
| 管理番号     | K0149621 ( 0 ) DR 1         |
| B Z 分類   | B Z 9                       |

| 器具効率     |           | 100 %           | 反射率             | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |      |  |  |
|----------|-----------|-----------------|-----------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|------|--|--|
|          |           |                 |                 | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |      |  |  |
|          |           |                 |                 | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |      |  |  |
| 上方光束     |           | 50 %            | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z CM |  |  |
| 下方光束     |           | 50 %            |                 |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |      |  |  |
| 保守率      |           | 良<br>中<br>否     | 0.63            | 0.6           | 44   | 32 | 23 | 18 | 40   | 29 | 22 | 16 | 33   | 24 | 18 | 14 | 26   | 19 | 14 | 11 | 6   |  |      |  |  |
|          |           |                 | 0.6             | 0.8           | 52   | 40 | 32 | 25 | 48   | 37 | 29 | 23 | 39   | 30 | 24 | 20 | 31   | 24 | 20 | 16 | 9   |  |      |  |  |
|          |           |                 | 0.56            | 1.0           | 58   | 46 | 38 | 31 | 53   | 43 | 35 | 29 | 44   | 35 | 29 | 24 | 35   | 28 | 23 | 20 | 12  |  |      |  |  |
|          |           |                 |                 | 1.25          | 64   | 53 | 44 | 38 | 58   | 48 | 41 | 35 | 48   | 40 | 34 | 29 | 38   | 32 | 28 | 24 | 15  |  |      |  |  |
| 下方投影面積   |           | cm <sup>2</sup> |                 | 1.5           | 68   | 57 | 49 | 43 | 62   | 53 | 45 | 40 | 51   | 44 | 38 | 33 | 41   | 36 | 31 | 27 | 17  |  |      |  |  |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0           | 74   | 64 | 57 | 51 | 67   | 59 | 53 | 47 | 56   | 49 | 44 | 40 | 45   | 40 | 36 | 33 | 21  |  |      |  |  |
| 取付<br>高さ | 器具間隔最大限   |                 |                 | 2.5           | 77   | 69 | 62 | 56 | 71   | 64 | 58 | 52 | 59   | 53 | 48 | 44 | 48   | 44 | 40 | 36 | 24  |  |      |  |  |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       | 3.0           | 80   | 73 | 66 | 61 | 74   | 67 | 61 | 56 | 61   | 56 | 52 | 48 | 50   | 46 | 43 | 40 | 26  |  |      |  |  |
| H m      | 1.82 H m  | 1.60 H m        |                 | 4.0           | 83   | 77 | 72 | 67 | 77   | 72 | 67 | 62 | 65   | 60 | 57 | 53 | 53   | 50 | 47 | 44 | 30  |  |      |  |  |
|          |           |                 |                 | 5.0           | 86   | 81 | 76 | 71 | 79   | 75 | 70 | 66 | 67   | 63 | 60 | 57 | 55   | 52 | 50 | 47 | 33  |  |      |  |  |
|          |           |                 |                 | 7.0           | 89   | 84 | 81 | 77 | 82   | 78 | 75 | 72 | 69   | 66 | 64 | 61 | 57   | 55 | 53 | 51 | 36  |  |      |  |  |
|          |           |                 |                 | 10.0          | 91   | 88 | 85 | 82 | 84   | 81 | 79 | 76 | 72   | 69 | 67 | 65 | 60   | 58 | 56 | 55 | 39  |  |      |  |  |

