

屋内照明器具特性	
品番 (品名)	L G W C 8 1 3 2 5 K
光源	LED5000_70_382 ×1 382.0 l m
管理番号	K0149620 (0) DR 1
B Z 分類	B Z 9

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		5 0 % 5 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 3	0 . 6	4 4	3 2	2 4	1 8	4 0	2 9	2 2	1 7	3 3	2 4	1 8	1 4	2 6	1 9	1 4	1 1	6
			0 . 6	0 . 8	5 2	4 0	3 2	2 5	4 8	3 7	2 9	2 3	3 9	3 0	2 4	2 0	3 1	2 5	2 0	1 6	9
			0 . 5 6	1 . 0	5 8	4 6	3 8	3 1	5 3	4 3	3 5	2 9	4 4	3 5	2 9	2 4	3 5	2 8	2 4	2 0	1 2
			1 . 2 5	1 . 5	6 4	5 3	4 4	3 8	5 8	4 8	4 1	3 5	4 8	4 0	3 4	2 9	3 8	3 2	2 8	2 4	1 5
下方投影面積		c m ²	2 . 0	7 4	6 4	5 7	5 1	6 7	5 9	5 3	4 7	5 6	5 0	4 4	4 0	4 5	4 0	3 6	3 3	2 1	
等価発光面積			c m ²	2 . 5	7 7	6 9	6 2	5 6	7 1	6 4	5 8	5 2	5 9	5 3	4 9	4 4	4 8	4 4	4 0	3 7	2 4
取付高さ	器具間隔最大限		3 . 0	8 0	7 3	6 6	6 1	7 4	6 7	6 1	5 7	6 1	5 6	5 2	4 8	5 0	4 6	4 3	4 0	2 7	
H m	1 . 8 8 H m	1 . 6 3 H m	4 . 0	8 3	7 7	7 2	6 7	7 7	7 2	6 7	6 2	6 5	6 0	5 7	5 3	5 3	5 0	4 7	4 4	3 0	
			5 . 0	8 6	8 1	7 6	7 2	7 9	7 5	7 0	6 6	6 7	6 3	6 0	5 7	5 5	5 2	5 0	4 7	3 3	
			7 . 0	8 9	8 4	8 1	7 7	8 2	7 8	7 5	7 2	6 9	6 7	6 4	6 1	5 7	5 5	5 3	5 1	3 6	
			1 0 . 0	9 1	8 8	8 5	8 2	8 4	8 1	7 9	7 6	7 2	6 9	6 7	6 5	6 0	5 8	5 6	5 5	3 9	

