

屋内照明器具特性	
品番 (品名)	L G W C 4 7 0 2 3
光源	L L D 2 0 0 0 L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 6 3 4 1 (0) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		68 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																
保守率		良 中 否	0 . 63	0 . 6	44	37	32	29	43	36	32	29	42	36	32	29	40	35	32	29	28
			0 . 6	0 . 8	51	45	40	37	50	44	40	37	48	43	40	37	47	43	39	37	35
			0 . 56	1 . 0	55	50	46	42	54	49	45	42	53	48	45	42	51	47	44	42	41
				1 . 25	59	54	50	47	58	53	50	47	56	52	49	47	55	51	49	46	45
下方投影面積		c m ²		1 . 5	61	57	53	51	60	56	53	50	59	55	52	50	57	54	52	50	48
			等価発光面積	c m ²	2 . 0	64	61	58	55	63	60	57	55	62	59	56	54	60	58	56	54
取付 高さ	器具間隔最大限			2 . 5	66	63	61	58	65	62	60	58	64	61	59	57	62	60	58	57	55
	横方向 (A)			縦方向 (B)		3 . 0	67	65	63	61	66	64	62	60	65	63	61	59	63	62	60
H m	1 . 17 H m	1 . 17 H m		4 . 0	69	67	65	63	68	66	64	63	66	65	63	62	65	63	62	61	60
				5 . 0	70	68	67	65	69	67	66	65	67	66	65	64	66	65	64	63	61
				7 . 0	71	70	68	67	70	69	68	67	68	67	67	66	67	66	65	65	63
				10 . 0	72	71	70	69	71	70	69	68	69	68	68	67	68	67	67	66	64

