

屋内照明器具特性	
品番 (品名)	NTN88007B
光源	LLD3020LCB1 ×1 795.0 l m
管理番号	K0179474 (0) DR 1
BZ分類	BZ1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		83 %																							
保守率		良	0.67	0.6	70	65	61	59	69	64	61	59	68	64	61	59	67	63	61	59	58				
		中	0.63	0.8	74	70	67	65	74	70	67	65	72	69	66	64	71	68	66	64	63				
		否	0.56	1.0	77	73	70	68	77	73	70	68	75	72	70	68	74	71	69	68	66				
				1.25	80	76	74	72	79	76	73	71	78	75	73	71	76	74	72	71	69				
下方投影面積		c m ²		1.5	82	78	76	74	81	78	76	74	79	77	75	73	78	76	74	73	71				
等価発光面積		c m ²		2.0	84	81	79	77	83	80	79	77	81	79	78	76	80	78	77	76	74				
取付高さ	器具間隔最大限			2.5	85	83	81	79	84	82	80	79	82	81	79	78	81	79	78	77	76				
	横方向 (A)		縦方向 (B)	3.0	86	84	82	81	85	83	82	80	83	82	81	79	82	80	79	78	77				
H m	0.41 H m		0.41 H m	4.0	87	85	84	83	86	85	83	82	84	83	82	81	83	82	81	80	78				
				5.0	87	86	85	84	86	85	84	84	85	84	83	82	83	82	82	81	79				
				7.0	88	87	86	86	87	86	86	85	85	85	84	84	84	83	83	82	80				
				10.0	89	88	87	87	88	87	87	86	86	85	85	85	84	84	83	83	81				

