

屋内照明器具特性	
品番 (品名)	NTN88007B
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0181922 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	44	36	31	27	44	36	31	27	42	35	30	27	40	34	30	27	26
			0.63	0.8	52	44	39	36	51	44	39	36	49	43	39	35	48	42	38	35	34
			0.56	1.0	57	50	45	42	56	50	45	41	54	48	44	41	52	47	44	41	39
				1.25	61	55	51	47	60	55	50	47	58	53	50	47	56	52	49	46	45
下方投影面積		cm ²		1.5	64	59	55	51	63	58	54	51	61	57	53	51	59	56	53	50	49
			等価発光面積	cm ²	2.0	68	64	60	57	67	63	59	57	65	61	59	56	63	60	58	56
取付 高さ	器具間隔最大限			2.5	70	66	63	61	69	66	63	60	67	64	62	60	65	63	61	59	57
	横方向 (A) 縦方向 (B)			3.0	72	69	66	63	71	68	65	63	69	66	64	62	67	65	63	61	60
H m	1.23 H m 1.23 H m			4.0	74	71	69	67	73	70	68	66	71	69	67	66	69	67	66	65	63
				5.0	75	73	71	69	74	72	70	69	72	70	69	68	70	69	68	67	65
				7.0	76	74	73	72	75	74	72	71	73	72	71	70	71	71	70	69	67
				10.0	77	76	75	74	76	75	74	73	74	73	73	72	72	72	71	71	69

