

屋内照明器具特性	
品番 (品名)	XLGB3309
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0179114 (0) DR 1
BZ分類	BZ5 / 1.8 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率		8 6 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
						室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 7	0 . 6	4 9	3 8	3 2	2 7	4 8	3 8	3 2	2 7	4 6	3 7	3 1	2 7	4 4	3 6	3 1	2 7	2 5					
			0 . 6 3	0 . 8	5 7	4 8	4 1	3 6	5 6	4 7	4 1	3 6	5 4	4 6	4 0	3 6	5 2	4 5	4 0	3 6	3 4					
			0 . 5 6	1 . 0	6 3	5 4	4 8	4 3	6 2	5 3	4 7	4 3	5 9	5 2	4 7	4 2	5 7	5 1	4 6	4 2	4 0					
			0 . 5 6	1 . 2 5	6 8	6 0	5 4	4 9	6 7	5 9	5 4	4 9	6 4	5 8	5 3	4 9	6 2	5 6	5 2	4 8	4 6					
下方投影面積		c m ²	1 . 5	7 2	6 4	5 9	5 4	7 0	6 4	5 8	5 4	6 8	6 2	5 7	5 3	6 5	6 0	5 6	5 3	5 1						
			2 . 0	7 7	7 1	6 5	6 1	7 5	7 0	6 5	6 1	7 3	6 8	6 4	6 0	7 0	6 6	6 3	6 0	5 7						
等価発光面積		c m ²	2 . 5	8 0	7 4	7 0	6 6	7 8	7 3	6 9	6 6	7 6	7 2	6 8	6 5	7 3	7 0	6 7	6 4	6 2						
			3 . 0	8 2	7 7	7 3	7 0	8 0	7 6	7 3	6 9	7 8	7 4	7 1	6 8	7 5	7 2	7 0	6 7	6 5						
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	8 4	8 1	7 8	7 5	8 3	8 0	7 7	7 4	8 1	7 8	7 5	7 3	7 8	7 6	7 4	7 2	7 0						
			5 . 0	8 6	8 3	8 0	7 8	8 5	8 2	8 0	7 7	8 2	8 0	7 8	7 6	8 0	7 8	7 6	7 5	7 2						
			7 . 0	8 8	8 6	8 4	8 2	8 7	8 5	8 3	8 1	8 4	8 3	8 1	7 9	8 2	8 1	7 9	7 8	7 6						
			1 0 . 0	8 9	8 8	8 6	8 5	8 8	8 7	8 5	8 4	8 6	8 5	8 3	8 2	8 4	8 3	8 2	8 1	7 8						

