

屋内照明器具特性	
品番 (品名)	L G B C 8 1 6 5 1
光源	LED2700_70_400 ×1 400.0 l m
管理番号	K0139440 (1) DR 1
B Z 分類	B Z 7 / 0 . 7 / B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		5 0 %																				
保守率		良 中 否	0 . 6 7	0 . 6	4 7	3 5	2 8	2 2	4 3	3 3	2 6	2 1	3 6	2 8	2 2	1 8	2 9	2 3	1 8	1 5	1 0	
			0 . 6 3	0 . 8	5 6	4 4	3 6	3 1	5 1	4 1	3 4	2 9	4 3	3 5	2 9	2 5	3 5	2 9	2 4	2 1	1 4	
			0 . 5 6	1 . 0	6 2	5 1	4 3	3 7	5 7	4 7	4 0	3 4	4 7	4 0	3 4	3 0	3 9	3 3	2 9	2 5	1 7	
				1 . 2 5	6 7	5 7	4 9	4 3	6 2	5 3	4 6	4 0	5 2	4 5	3 9	3 5	4 2	3 7	3 3	2 9	2 0	
下方投影面積		cm ²	1 . 5	7 1	6 2	5 4	4 8	6 5	5 7	5 0	4 5	5 5	4 8	4 3	3 9	4 5	4 0	3 6	3 3	2 3		
等価発光面積		cm ²	2 . 0	7 6	6 8	6 2	5 6	7 0	6 3	5 7	5 2	5 9	5 4	4 9	4 5	4 9	4 4	4 1	3 8	2 7		
取付 高さ	器具間隔最大限		2 . 5	8 0	7 3	6 7	6 1	7 4	6 7	6 2	5 7	6 2	5 7	5 3	4 9	5 1	4 8	4 4	4 2	2 9		
	横方向 (A) 縦方向 (B)		3 . 0	8 2	7 6	7 0	6 6	7 6	7 0	6 6	6 1	6 4	6 0	5 6	5 3	5 3	5 0	4 7	4 4	3 1		
H m	0 . 0 0 H m	1 . 8 5 H m	4 . 0	8 5	8 0	7 6	7 1	7 9	7 5	7 0	6 7	6 7	6 3	6 0	5 7	5 6	5 3	5 0	4 8	3 4		
			5 . 0	8 8	8 3	7 9	7 5	8 1	7 7	7 4	7 0	6 9	6 6	6 3	6 0	5 7	5 5	5 3	5 1	3 6		
			7 . 0	9 0	8 7	8 3	8 0	8 4	8 0	7 8	7 5	7 1	6 9	6 7	6 4	5 9	5 8	5 6	5 4	3 9		
			1 0 . 0	9 2	8 9	8 7	8 4	8 5	8 3	8 1	7 9	7 3	7 1	6 9	6 8	6 1	6 0	5 8	5 7	4 2		

