

屋内照明器具特性	
品番 (品名)	NTN88081W
光源	LLD2000MLCE1 ×1 531.0 lm
管理番号	K0179224 (0) DR 1
BZ分類	BZ5

器具効率		98 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.69	0.6	54	42	35	29	53	41	34	29	50	40	33	29	47	39	33	28	26
			0.67	0.8	64	52	45	39	62	51	44	39	59	50	43	38	56	48	42	37	35
			0.63	1.0	70	60	52	46	68	58	51	46	65	56	50	45	61	54	49	44	41
				1.25	76	66	59	53	74	65	58	53	70	63	57	52	67	60	55	51	48
下方投影面積		cm ²	1.5	80	71	64	59	78	70	63	58	74	67	62	57	71	65	60	56	53	
			等価発光面積		cm ²	2.0	86	78	72	67	84	77	71	66	80	74	69	65	76	71	67
取付 高さ	器具間隔最大限		2.5	89	83	77	73	87	81	76	72	83	78	74	70	79	75	72	68	65	
	横方向 (A)	縦方向 (B)	3.0	92	86	81	77	89	84	80	76	86	81	77	74	82	78	75	72	68	
H m	1.27 H m	1.27 H m	4.0	95	90	86	83	93	89	85	81	89	85	82	79	85	82	80	77	73	
			5.0	97	93	89	86	95	91	88	85	91	88	85	83	87	85	83	81	77	
			7.0	99	96	93	91	97	94	92	90	93	91	89	87	90	88	86	85	80	
			10.0	101	98	97	95	99	97	95	93	95	93	92	90	92	90	89	88	84	

