

屋内照明器具特性	
品番 (品名)	L G W5 1 7 6 9 W
光源	L L D4 0 0 0 L C B1 ×1 845.0 l m
管理番号	K0182072 (0) D R 1
B Z 分類	B Z 5

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	41	31	25	21	39	30	25	21	36	29	24	20	33	27	23	19	17
			0.6	0.8	48	39	33	28	46	38	32	28	43	36	31	27	40	34	29	26	23
			0.56	1.0	53	45	38	34	51	43	38	33	47	41	36	32	44	38	34	31	28
				1.25	58	50	44	39	55	48	43	39	51	45	41	37	48	43	39	36	32
下方投影面積 等価発光面積		cm ² cm ²		1.5	61	54	48	44	59	52	47	43	54	49	45	41	50	46	42	39	36
				2.0	65	59	54	50	63	57	53	49	58	54	50	47	54	51	47	45	41
				2.5	68	63	58	54	65	61	57	53	61	57	54	51	57	54	51	48	44
				3.0	70	65	61	58	67	63	60	56	63	60	56	54	59	56	54	51	47
H m	1.30 H m	1.30 H m		4.0	72	69	65	62	70	67	63	61	65	63	60	58	61	59	57	55	50
				5.0	74	71	68	65	71	69	66	64	67	65	63	61	63	61	59	58	53
				7.0	76	73	71	69	73	71	69	67	69	67	65	64	65	63	62	61	56
				10.0	77	75	74	72	75	73	72	70	70	69	68	67	66	65	64	63	58

