

屋内照明器具特性	
品番 (品名)	L G W5 1 7 6 9 W
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 2 0 7 3 (0) D R 1
B Z 分類	B Z 5

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 3	0 . 6	4 3	3 3	2 7	2 2	4 2	3 2	2 6	2 2	3 8	3 0	2 5	2 1	3 6	2 9	2 4	2 0	1 8	
			0 . 6	0 . 8	5 1	4 2	3 5	3 0	4 9	4 0	3 4	3 0	4 5	3 8	3 3	2 9	4 2	3 6	3 1	2 7	2 5	
			0 . 5 6	1 . 0	5 6	4 7	4 1	3 6	5 4	4 6	4 0	3 5	5 0	4 3	3 8	3 4	4 6	4 1	3 6	3 3	2 9	
				1 . 2 5	6 1	5 3	4 7	4 2	5 9	5 1	4 6	4 1	5 5	4 8	4 3	3 9	5 1	4 5	4 1	3 8	3 4	
下方投影面積		c m ²	1 . 5	6 5	5 7	5 1	4 6	6 2	5 5	5 0	4 5	5 8	5 2	4 7	4 4	5 4	4 9	4 5	4 2	3 8		
等価発光面積				c m ²	2 . 0	6 9	6 3	5 7	5 3	6 7	6 1	5 6	5 2	6 2	5 7	5 3	5 0	5 8	5 4	5 0	4 7	4 3
取付高さ	器具間隔最大限				2 . 5	7 2	6 6	6 2	5 8	7 0	6 4	6 0	5 6	6 5	6 1	5 7	5 4	6 1	5 7	5 4	5 1	4 7
	横方向 (A)		縦方向 (B)		3 . 0	7 4	6 9	6 5	6 1	7 2	6 7	6 3	6 0	6 7	6 3	6 0	5 7	6 3	6 0	5 7	5 4	5 0
H m	1 . 3 0 H m		1 . 3 0 H m		4 . 0	7 7	7 3	6 9	6 6	7 4	7 1	6 7	6 5	7 0	6 7	6 4	6 1	6 5	6 3	6 1	5 9	5 4
					5 . 0	7 8	7 5	7 2	6 9	7 6	7 3	7 0	6 8	7 1	6 9	6 6	6 4	6 7	6 5	6 3	6 1	5 6
					7 . 0	8 0	7 8	7 5	7 3	7 8	7 6	7 3	7 1	7 3	7 1	7 0	6 8	6 9	6 7	6 6	6 4	5 9
					1 0 . 0	8 2	8 0	7 8	7 6	7 9	7 8	7 6	7 4	7 5	7 3	7 2	7 1	7 0	6 9	6 8	6 7	6 2

