

屋内照明器具特性	
品番 (品名)	L G W5 1 7 6 9 B
光源	L L D4 0 0 0 L C B1 ×1 8 4 5 . 0 l m
管理番号	K 0 1 8 2 0 5 5 (0) D R 1
B Z 分類	B Z 5

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		11 %	室指数	照明率 (X 0 . 0 1)																	Z	C	M
下方光束		66 %																					
保守率		良 中 否	0.63	0.6	41	31	25	21	39	30	25	21	36	29	24	20	34	27	23	19	17		
			0.6	0.8	48	39	33	28	46	38	32	28	43	36	31	27	40	34	29	26	23		
				1.0	53	45	38	34	51	43	38	33	47	41	36	32	44	38	34	31	28		
			0.56	1.25	58	50	44	39	55	48	43	39	51	45	41	37	48	43	39	36	32		
下方投影面積		c m ²		1.5	61	54	48	44	59	52	47	43	54	49	45	41	51	46	42	39	36		
				2.0	65	59	54	50	63	57	53	49	59	54	50	47	55	51	48	45	41		
取付 高さ	器具間隔最大限			2.5	68	63	58	54	66	61	57	53	61	57	54	51	57	54	51	49	44		
	横方向 (A)		縦方向 (B)	3.0	70	65	61	58	67	63	60	56	63	60	57	54	59	56	54	51	47		
H m	1.31 H m	1.31 H m		4.0	72	69	65	62	70	67	64	61	66	63	60	58	62	59	57	55	51		
				5.0	74	71	68	65	72	69	66	64	67	65	63	61	63	61	59	58	53		
				7.0	76	73	71	69	73	71	69	67	69	67	66	64	65	64	62	61	56		
				10.0	77	75	74	72	75	73	72	70	71	69	68	67	67	65	64	63	58		

