

屋内照明器具特性	
品番 (品名)	L G W5 1 7 7 9 Y
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0181607 (0) DR 1
B Z 分類	BZ5 / 0.9 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率		65 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01) Z C M																			
保守率		良 中 否	0.63	0.6	37	30	25	21	37	29	24	21	35	29	24	21	34	28	24	21	20					
			0.6	0.8	44	37	32	28	43	36	31	28	41	35	31	28	40	34	31	28	26					
			0.56	1.0	48	41	37	33	47	41	36	33	45	40	36	33	44	39	35	32	31					
				1.25	52	46	41	38	51	45	41	38	49	44	40	37	47	43	40	37	36					
下方投影面積		c m ²	1.5	55	49	45	41	54	49	44	41	52	47	44	41	50	46	43	40	39						
				等価発光面積	2.0	58	54	50	47	57	53	49	47	55	52	49	46	54	50	48	45	44				
取付高さ	器具間隔最大限			2.5	61	57	53	50	60	56	53	50	58	55	52	50	56	53	51	49	47					
	横方向 (A)		縦方向 (B)	3.0	62	59	56	53	61	58	55	53	59	57	54	52	58	55	53	51	50					
H m	1.22 H m	1.22 H m	4.0	64	61	59	57	63	61	58	56	61	59	57	56	60	58	56	55	53						
			5.0	65	63	61	59	64	62	60	59	63	61	59	58	61	60	58	57	55						
			7.0	67	65	64	62	66	64	63	62	64	63	62	61	63	61	60	59	58						
			10.0	68	67	66	64	67	66	65	64	65	64	64	63	64	63	62	62	60						

